



Performance. Power.  
Productivity.™

# SLS18Mg

## 18 Ga. 1/4" Crown 1-5/8" Stapler

SLS18Mg's magnesium body delivers an ultra light tool with SENCO dependability. The oil free design, selective trigger, rear exhaust and rotating belt hook combine to provide a tool that will perform the toughest jobs while delivering professional results and comfortable operation.



### Applications


Cabinets, Soffit, Drawer Assembly, Picture Frames, Case Backs, Craft Assembly

### Features and Benefits

- Magnesium mainbody provides a durable and ultra light tool for comfortable extended use.
- Oil free motor eliminates oil carryover onto the work surface, protecting your hard work.
- Metal cylinder for increased durability.
- Selectable trigger lets you control the fastening method with the flip of a switch.
- Rotatable rear exhaust and belt hook keeps dust and debris off the work surface while keeping your tool at the ready.
- Over-molded rubber grip, swivel plug and reload indicator will keep you working comfortably and efficiently throughout the day.
- Includes case, swivel plug and wrench.

### Specifications

Item#	1W0021N
Trigger	Selectable actuation
Reg. Operating Pressure	70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.)	2.4 scfm
Air Inlet	1/4" NPT
Tool Weight	2.6 lbs (1.8 kg)
Height	9.5" (241 mm)
Length	10.25" (260 mm)
Width	2.5" (63.5 mm)



### Fastener Specifications

Gauge	.18
Fastener Capacity	110
Fastener Range	3/8" - 1-5/8"
Crown	1/4"
Finish	Bright Basic, Galv. & Stainless
Collation	Glued strip

### SENCO® 18 Ga. 1/4" Crown Medium Wire

Length	Item Code	Box Count	Point	Finish	Coating	Package
3/4	L11BRB	5.M	Chisel	Bright	Sencote	Box
1	L13BRBN	5.M	Chisel	Bright	Sencote	Box
1	L13BRBP	5.M	Chisel	Bright	Sencote	Box
1 1/8	L14BRB	5.M	Chisel	Bright	Sencote	Box
1 1/4	L15BRB	5.M	Chisel	Bright	Sencote	Box
3/8	L06BAB	10.M	Chisel	Galv	Sencote	Box
7/16	L07BABP	24.M	Chisel	Galv	Sencote	Box
7/16	L07BQBP	24.M	Chisel	Class1 Galv	Sencote	Box
1/2	L08BAB	10.M	Chisel	Galv	Sencote	Box
5/8	L10BABN	5.M	Chisel	Galv	Sencote	Box
5/8	L10HABN	5.M	Cross Cut Chisel	Galv	Sencote	Box
3/4	L11BAB	5.M	Chisel	Galv	Sencote	Box
3/4	L11HAB	5.M	Cross Cut Chisel	Galv	Sencote	Box
7/8	L12BAB	5.M	Chisel	Galv	Sencote	Box
7/8	L12BQB	5.M	Chisel	Class1 Galv	Sencote	Box
1	L13BABN	5.M	Chisel	Galv	Sencote	Box
1	L13HABN	5.M	Cross Cut Chisel	Galv	Sencote	Box
1 1/8	L14BAB	5.M	Chisel	Galv	Sencote	Box
1 1/4	L15BAB	5.M	Chisel	Galv	Sencote	Box
1 1/2	L17BAB	5.M	Chisel	Galv	Sencote	Box
5/8	A800629	1.2M	Chisel	Galv	Sencote	Clamshell
3/4	A800759	.9M	Chisel	Galv	Sencote	Clamshell
1	A801009	.9M	Chisel	Galv	Sencote	Clamshell
1 1/4	A801259	.7M	Chisel	Galv	Sencote	Clamshell
1 1/2	A801509	.6M	Chisel	Galv	Sencote	Clamshell
Variety	A809909	.9M	Chisel	Galv	Sencote	Clamshell

The A809909 variety packs contain 900 assorted 1/2", 1" and 1-1/2" 18 gauge 1/4" crown staples.

3/4	L11BGA	5.M	Chisel	Stainless	Plain	Box
1 1/8	L14BGA	5.M	Chisel	Stainless	Plain	Box

## SLS18Mg Features



\*Choose the right actuation mode!

Sequential Actuation (also known as restrictive trigger or trigger fire) operates in the following sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tool to ensure proper use and safety precautions. For additional information on trigger systems and how Senco will save you time, reduce costs and increase quality, call our toll-free Action Line: 800-543-4596, or visit our website at: [www.senco.com](http://www.senco.com)