

The DuraSpin Collated Screw Fastening System Family is the professionals choice for demanding steel framing, drywall and wood fastening applications. The perfect solution for high productivity crews as well as a single man operation. Like having an extra hand, Senco DuraSpin will dramatically increase your productivity.



**DURASPIN**

Collated screw fastening systems



**USE SENCO TOOLS**



# COLLATED SCREW SYSTEMS

SENCO®

## HEAVY DUTY MACHINE DS5525-18V



### TECHNICAL INFORMATION

|                   |                |
|-------------------|----------------|
| LxWxH             | 381x86x241 mm  |
| Weight            | 2,6 kg         |
| RPM               | 2500           |
| Torque            | 8Nm            |
| Magazine capacity | 50             |
| Max. screw length | 55mm           |
| Battery           | 18V 3Ah Li-ion |
| Screw per charge  | up to 1400     |
| Recharge time     | 1 hour         |


### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

| DESCRIPTION   | ART. NR |
|---------------|---------|
| DS5525-18V EU | 7X2001N |
| DS5525-18V UK | 7X7001N |



\* 13-50 mm screws require special nosepiece

## HEAVY DUTY MACHINE DS5525-AC



### TECHNICAL INFORMATION

|                   |               |
|-------------------|---------------|
| LxWxH             | 425x70x233 mm |
| Weight            | 2,1 kg        |
| RPM               | 2500          |
| Torque            | 11Nm          |
| Magazine capacity | 50            |
| Max. screw length | 55mm          |

### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

| DESCRIPTION         | ART. NR |
|---------------------|---------|
| DS5525-AC EU        | 7U2001N |
| DS5525-AC UK (230V) | 7U7001N |
| DS5525-AC UK (110V) | 7U7002N |



\* 13-50 mm screws require special nosepiece

## HIGH SPEED MACHINE DS5550-18V



### TECHNICAL INFORMATION

|                   |                |
|-------------------|----------------|
| LxWxH             | 381x86x241 mm  |
| Weight            | 2,6 kg         |
| RPM               | 5000           |
| Torque            | 5Nm            |
| Magazine capacity | 50             |
| Max. screw length | 55mm           |
| Battery           | 18V 3Ah Li-ion |
| Screw per charge  | up to 1400     |
| Recharge time     | 1 hour         |


### APPLICATIONS

Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

### FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

| DESCRIPTION   | ART. NR |
|---------------|---------|
| DS5550-18V EU | 7W2001N |
| DS5550-18V UK | 7W7001N |



\* 13-50 mm screws require special nosepiece

## HIGH SPEED MACHINE DS5550-AC



### TECHNICAL INFORMATION

|                   |               |
|-------------------|---------------|
| LxWxH             | 425x70x233 mm |
| Weight            | 2,1 kg        |
| RPM               | 5000          |
| Torque            | 7Nm           |
| Magazine capacity | 50            |
| Max. screw length | 55mm          |


### APPLICATIONS

Drywall to wood or steel studs, subfloor, sheathing, cement board, underlayment

### FEATURES

- 5000 RPM high speed motor
- Patent pending corner-fit system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change

| DESCRIPTION         | ART. NR |
|---------------------|---------|
| DS5550-AC EU        | 7T2001N |
| DS5550-AC UK (230V) | 7T7001N |
| DS5550-AC UK (110V) | 7T7002N |



\* 13-50 mm screws require special nosepiece

## MULTI PURPOSE MACHINE DS7525-18V



### TECHNICAL INFORMATION

|                   |                |
|-------------------|----------------|
| LxWxH             | 394x86x241 mm  |
| Weight            | 2,7 kg         |
| RPM               | 2500           |
| Torque            | 8Nm            |
| Magazine capacity | 50             |
| Max. screw length | 75mm           |
| Battery           | 18V 3Ah Li-ion |
| Screw per charge  | up to 1400     |
| Recharge time     | 1 hour         |

### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

| DESCRIPTION   | ART. NR |
|---------------|---------|
| DS7525-18V EU | 7Y2001N |
| DS7525-18V UK | 7Y7001N |



\* 13-50 mm screws require special nosepiece

## MULTI PURPOSE MACHINE DS7525-AC



### TECHNICAL INFORMATION

|                   |               |
|-------------------|---------------|
| LxWxH             | 438x70x233 mm |
| Weight            | 2,2 kg        |
| RPM               | 2500          |
| Torque            | 11Nm          |
| Magazine capacity | 50            |
| Max. screw length | 75mm          |


### APPLICATIONS

Drywall to wood or steel studs, sub-floor, cement board, underlayment, sheathing to steel, metal framing

### FEATURES

- 2500 RPM high torque motor
- Patent pending corner-fit system
- Patented sliding screw guide
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock

| DESCRIPTION         | ART. NR |
|---------------------|---------|
| DS7525-AC EU        | 7V2001N |
| DS7525-AC UK (230V) | 7V7001N |
| DS7525-AC UK (110V) | 7V7002N |



\* 13-50 mm screws require special nosepiece



# COLLATED SCREW SYSTEMS & ACCESSORIES

**SENCO**

## EASY DRIVER SCREW SYSTEM DS300-AC



### TECHNICAL INFORMATION

|                   |                     |
|-------------------|---------------------|
| LxWxH             | 800-1054x109x175 mm |
| Weight            | 3,9 kg              |
| RPM               | 3300                |
| Torque            | 6Nm                 |
| Magazine capacity | 50                  |
| Max. screw length | 75mm                |

### APPLICATIONS

Decking, subfloors

### FEATURES

- Depth adjustment allows precise countersinking of screws
- Trigger lock
- Height adjustable handle
- Patented clutch design for long-lasting durability

| DESCRIPTION        | ART. NR |
|--------------------|---------|
| DS300-AC EU (230V) | 1P2001N |
| DS300-AC UK (230V) | 1P7001N |
| DS300-AC UK (110V) | 1P7002N |



## ROOFING SCREW SYSTEM DS300-AC



### TECHNICAL INFORMATION

|                   |                     |
|-------------------|---------------------|
| LxWxH             | 800-1054x109x175 mm |
| Weight            | 3,9 kg              |
| RPM               | 3300                |
| Torque            | 6Nm                 |
| Magazine capacity | 50                  |
| Max. screw length | 75mm                |


### APPLICATIONS

Specially designed for roofing application

### FEATURES

- Specifically designed for roofing
- Adjustable depth of drive
- Height adjustable handle
- Trigger lock
- Patented clutch design for long-lasting durability

| DESCRIPTION             | ART. NR  |
|-------------------------|----------|
| DS300-AC roofing (230V) | 1P2001NX |



## DURASPIN BATTERIES



| DESCRIPTION                        | ART. NR. |
|------------------------------------|----------|
| Duraspin battery 18V Li-ion 1,5 Ah | VB0160EU |
| Duraspin battery 18V Li-ion 3,0 Ah | VB0162EU |

## DURASPIN CHARGERS



| DESCRIPTION            | ART. NR. |
|------------------------|----------|
| Battery charger 18V EU | VB0157   |
| Battery charger 18V UK | VB0159   |

## NOSE PIECES



| DESCRIPTION            | ART.NR.  |
|------------------------|----------|
| Nose piece for drywall |          |
| DS5525/DS5550          | FC0886EU |
| DS7525                 | FC0906EU |



| DESCRIPTION         | ART.NR.  |
|---------------------|----------|
| Nose piece for wood |          |
| DS5525/DS5550       | FB0162EU |
| DS7525              | FB0160EU |

## DRIVE BITS IN BLISTERPACK



| DESCRIPTION                    | ART.NR.   |
|--------------------------------|-----------|
| <b>BITS FOR DS5525, DS5550</b> |           |
| Screw bit PH2                  | EA0326B   |
| Screw bit SQ2                  | EA0327B   |
| Screw bit PZ2                  | EA0335B*  |
| Screw bit TX20                 | EA0336B*  |
| Screw bit Senco drive          | EA0333B*  |
| <b>BITS FOR DS7525</b>         |           |
| Screw bit PH2                  | EA0329B   |
| Screw bit SQ2                  | EA0330B   |
| Screw bit PZ2                  | EA0337B*  |
| Screw bit TX20                 | EA0338B*  |
| Screw bit Senco drive          | EA0334B*  |
| <b>BITS FOR DS300AC</b>        |           |
| Screw bit PH2                  | EAP27530B |
| Screw bit SQ2                  | EAS27530B |
| Screw bit PZ2                  | EAP227530 |
| Screw bit Senco drive          | EA0127TB  |

\* article could have longer delivery time






# COLLATED SCREWS




## INDEX


### SCREW HEAD




### SCREW POINT



### RECESS



### SCREW THREAD





### MATERIAL/ FINISH

- Phosphate
- Clear zinc
- Yellow zinc
- Green ruspert II
- Stainless Steel
- Weatherex II



Items marked \* could have a longer lead time.

## DRYWALL TO WOOD





| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|--------------|-----------------|-----------|-------------|
| ○ 3,9 x 30mm | Clear Zinc      | 8,00-8,50 | 39N30MC-5   |
| ○ 3,9 x 42mm | Clear Zinc      | 8,00-8,50 | 39N42MC-5 * |
| ○ 3,9 x 55mm | Clear Zinc      | 8,00-8,50 | 39N55MC-5 * |

## DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)



| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|--------------|-----------------|-----------|-------------|
| ○ 3,9 x 30mm | Clear Zinc      | 6,00-6,50 | 39T30MC-5 * |
| ○ 3,9 x 40mm | Clear Zinc      | 6,00-6,50 | 39T40MC-5 * |
| ○ 3,9 x 50mm | Clear Zinc      | 6,00-6,50 | 39T50MC-5 * |

## DRYWALL TO LIGHT STEEL (UP TO 1MM)




| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|--------------|-----------------|-----------|-------------|
| ○ 3,5 x 25mm | Clear Zinc      | 8,00-8,50 | 35P25MC-5 * |
| ○ 3,5 x 40mm | Clear Zinc      | 8,00-8,50 | 35P40MC-5   |

## DRYWALL TO LIGHT STEEL (UP TO 1MM)



| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|--------------|-----------------|-----------|-----------|
| ○ 3,5 x 35mm | Phosphate       | 8,00-8,50 | 35B35MP   |
| ○ 3,5 x 45mm | Phosphate       | 8,00-8,50 | 35B45MP   |
| ○ 3,9 x 25mm | Phosphate       | 8,00-8,50 | 39B25MP   |
| ○ 3,9 x 35mm | Phosphate       | 8,00-8,50 | 39B35MP   |
| ○ 3,9 x 45mm | Phosphate       | 8,00-8,50 | 39B45MP   |
| ○ 3,9 x 55mm | Phosphate       | 8,00-8,50 | 39B55MP * |

## DRYWALL TO HEAVY STEEL (UP TO 3MM)




| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|--------------|-----------------|-----------|-----------|
| ○ 3,5 x 25mm | Phosphate       | 8,00-8,47 | 35Q25MP * |
| ○ 3,5 x 35mm | Phosphate       | 8,00-8,48 | 35Q35MP * |
| ○ 3,5 x 40mm | Phosphate       | 8,00-8,49 | 35Q40MP * |
| ○ 3,5 x 45mm | Phosphate       | 8,00-8,50 | 35Q45MP * |

|              |            |           |             |
|--------------|------------|-----------|-------------|
| ○ 3,5 x 25mm | Clear Zinc | 8,00-8,50 | 35Q25MC-5   |
| ○ 3,5 x 35mm | Clear Zinc | 8,00-8,50 | 35Q35MC-5   |
| ○ 3,5 x 40mm | Clear Zinc | 8,00-8,50 | 35Q40MC-5 * |
| ○ 3,5 x 45mm | Clear Zinc | 8,00-8,50 | 35Q45MC-5   |



## DRYWALL TO WOOD



| SIZE         | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|--------------|-----------------|-----------|-------------|
| ○ 3,9 x 25mm | Phosphate       | 8,00-8,50 | 39A25MP     |
| ○ 3,9 x 30mm | Phosphate       | 8,00-8,50 | 39A30MP     |
| ○ 3,9 x 35mm | Phosphate       | 8,00-8,50 | 39A35MP     |
| ○ 3,9 x 41mm | Phosphate       | 8,00-8,50 | 39A41MP *   |
| ○ 3,9 x 45mm | Phosphate       | 8,00-8,50 | 39A45MP     |
| ○ 3,9 x 50mm | Phosphate       | 8,00-8,50 | 39A50MP     |
| ○ 3,9 x 55mm | Phosphate       | 8,00-8,50 | 39A55MP     |
| ○ 4,5 x 75mm | Phosphate       | 8,00-8,50 | 45A75MP     |
| ○ 3,9 x 32mm | Clear Zinc      | 8,00-8,50 | 39A32MC-5   |
| ○ 3,9 x 35mm | Clear Zinc      | 8,00-8,50 | 39A35MC-5 * |
| ○ 3,9 x 42mm | Clear Zinc      | 8,00-8,50 | 39A42MC-5   |
| ○ 3,9 x 55mm | Clear Zinc      | 8,00-8,50 | 39A55MC-5 * |



USE SENCO FASTENERS

# COLLATED SCREWS




**SENCO**<sup>®</sup>

## DRYWALL TO WOOD OR LIGHT STEEL (UP TO 1MM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|------------|-----------------|-----------|-------------|
| 3,9 x 25mm | Phosphate       | 8,00-8,45 | 39S25MP *   |
| 3,9 x 35mm | Phosphate       | 8,00-8,50 | 39S35MP *   |
| 3,9 x 40mm | Phosphate       | 8,00-8,47 | 39S40MP *   |
| 3,9 x 45mm | Phosphate       | 8,00-8,48 | 39S45MP *   |
| 3,9 x 55mm | Phosphate       | 8,00-8,48 | 39S55MP *   |
| 3,9 x 25mm | Clear Zinc      | 8,00-8,50 | 39S25MC-5 * |
| 3,9 x 30mm | Clear Zinc      | 8,00-8,50 | 39S30MC-5 * |
| 3,9 x 32mm | Clear Zinc      | 8,00-8,50 | 39S32MC-5   |
| 3,9 x 35mm | Clear Zinc      | 8,00-8,50 | 39S35MC-5   |
| 3,9 x 40mm | Clear Zinc      | 8,00-8,50 | 39S40MC-5 * |
| 3,9 x 42mm | Clear Zinc      | 8,00-8,50 | 39S42MC-5   |
| 3,9 x 50mm | Clear Zinc      | 8,00-8,50 | 39S50MC-5 * |

## GYPSUM FIBER BOARD TO WOOD OR LIGHT STEEL (UP TO 1MM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.     |
|------------|-----------------|-----------|-------------|
| 3,9 x 30mm | Clear Zinc      | 6,00-6,50 | 39U30MC-5 * |
| 3,9 x 40mm | Clear Zinc      | 6,00-6,50 | 39U40MC-5 * |
| 3,9 x 50mm | Clear Zinc      | 6,00-6,50 | 39U50MC-5 * |

## GENERAL WOOD TO WOOD



| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,0 x 25mm | Clear Zinc      | 8,00-8,50 | 40K25MC * |
| 4,0 x 30mm | Clear Zinc      | 8,00-8,50 | 40K30MC * |
| 4,0 x 35mm | Clear Zinc      | 8,00-8,50 | 40K35MC * |
| 4,0 x 40mm | Clear Zinc      | 8,00-8,50 | 40K40MC * |
| 4,0 x 45mm | Clear Zinc      | 8,00-8,50 | 40K45MC * |
| 4,0 x 50mm | Clear Zinc      | 8,00-8,50 | 40K50MC * |
| 4,0 x 55mm | Clear Zinc      | 8,00-8,50 | 40K55MC * |
| 4,0 x 60mm | Clear Zinc      | 8,00-8,50 | 40K60MC * |
| 4,2 x 25mm | Yellow Zinc     | 8,00-8,50 | 42K25MY   |
| 4,2 x 30mm | Yellow Zinc     | 8,00-8,50 | 42K30MY   |
| 4,2 x 35mm | Yellow Zinc     | 8,00-8,50 | 42K35MY   |
| 4,2 x 45mm | Yellow Zinc     | 8,00-8,50 | 42K45MY   |

## FLOORING WOOD TO WOOD (CHIPBOARD)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,0 x 25mm | Clear Zinc      | 8,00-8,50 | 40H25MC * |
| 4,0 x 30mm | Clear Zinc      | 8,00-8,50 | 40H30MC * |
| 4,0 x 35mm | Clear Zinc      | 8,00-8,50 | 40H35MC   |
| 4,0 x 40mm | Clear Zinc      | 8,00-8,50 | 40H40MC   |
| 4,0 x 45mm | Clear Zinc      | 8,00-8,50 | 40H45MC * |
| 4,0 x 50mm | Clear Zinc      | 8,00-8,50 | 40H50MC * |
| 4,0 x 55mm | Clear Zinc      | 8,00-8,50 | 40H55MC * |
| 4,0 x 60mm | Clear Zinc      | 8,00-8,50 | 40H60MC * |
| 4,2 x 25mm | Yellow Zinc     | 8,00-8,50 | 42H25MY * |
| 4,2 x 30mm | Yellow Zinc     | 8,00-8,50 | 42H30MY * |
| 4,2 x 35mm | Yellow Zinc     | 8,00-8,50 | 42H35MY * |
| 4,2 x 45mm | Yellow Zinc     | 8,00-8,50 | 42H45MY * |

## GYPSUM FIBER BOARD TO LIGHT STEEL (UP TO 1MM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR. |
|------------|-----------------|-----------|---------|
| 3,9 x 30mm | Phosphate       | 6,70-7,00 | 39J30MP |
| 3,9 x 45mm | Phosphate       | 6,70-7,00 | 39J45MP |

## HARD FIBER TO WOOD OR LIGHT STEEL (UP TO 1MM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 3,9 x 30mm | Clear Zinc      | 6,70-7,00 | 39JS30MC * |
| 3,9 x 45mm | Clear Zinc      | 6,70-7,00 | 39JS45MC * |

## HARD FIBER BOARD TO LIGHT STEEL (UP TO 1MM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,2 x 35mm | Phosphate       | 7,40-7,80 | 42UM35MP * |
| 4,2 x 38mm | Phosphate       | 7,40-7,80 | 42UM38MP   |

## WOOD TO WOOD (CHIPBOARD)



| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,2 x 35mm | Yellow Zinc     | 8,00-8,50 | 42KS35MY * |
| 4,2 x 40mm | Yellow Zinc     | 8,00-8,50 | 42KS40MY * |
| 4,2 x 45mm | Yellow Zinc     | 8,00-8,50 | 42KS45MY * |
| 4,2 x 50mm | Yellow Zinc     | 8,00-8,50 | 42KS50MY * |

## FLOORING WOOD TO WOOD



| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR. |
|------------|-----------------|-----------|---------|
| 4,5 x 75mm | Yellow Zinc     | 8,00-8,50 | 45F75MY |

**USE SENCO FASTENERS**




# COLLATED SCREWS





**SENCO**<sup>®</sup>

## FLOORING WOOD TO WOOD




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,5 x 60mm | Yellow Zinc     | 8,00-8,50 | 45X60MY   |
| 4,5 x 65mm | Yellow Zinc     | 8,00-8,50 | 45X65MY * |
| 4,5 x 70mm | Yellow Zinc     | 8,00-8,50 | 45X70MY * |

## FLOORING WOOD TO WOOD





| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,2 x 35mm | Yellow Zinc     | 7,00-7,50 | 42Z35MY * |
| 4,2 x 45mm | Yellow Zinc     | 7,00-7,50 | 42Z45MY * |
| 4,2 x 55mm | Yellow Zinc     | 7,00-7,50 | 42Z55MY   |

## DECKING WOOD TO WOOD





| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,5 x 50mm | Stainless Steel | 8,00-8,50 | 45D50MSA * |
| 4,5 x 65mm | Stainless Steel | 8,00-8,50 | 45D65MSA   |
| 4,5 x 75mm | Stainless Steel | 8,00-8,50 | 45D75MSA * |

## FLOORING/DECKING WOOD TO WOOD (SOFT)





| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,2 x 35mm | Yellow Zinc     | 8,00-8,50 | 42Y35MY * |
| 4,2 x 40mm | Yellow Zinc     | 8,00-8,50 | 42Y40MY * |
| 4,2 x 50mm | Yellow Zinc     | 8,00-8,50 | 42Y50MY * |
| 4,2 x 55mm | Yellow Zinc     | 8,00-8,50 | 42Y55MY   |

## FLOORING WOOD TO WOOD (MEDIUM)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.   |
|------------|-----------------|-----------|-----------|
| 4,2 x 25mm | Yellow Zinc     | 7,00-7,50 | 42R25MY * |
| 4,2 x 35mm | Yellow Zinc     | 7,00-7,50 | 42R35MY * |
| 4,2 x 40mm | Yellow Zinc     | 7,00-7,50 | 42R40MY * |
| 4,2 x 45mm | Yellow Zinc     | 7,00-7,50 | 42R45MY   |
| 4,2 x 50mm | Yellow Zinc     | 7,00-7,50 | 42R50MY   |
| 4,2 x 55mm | Yellow Zinc     | 7,00-7,50 | 42R55MY * |
| 4,5 x 75mm | Yellow Zinc     | 7,00-7,50 | 45R75MY * |
| 4,2 x 40mm | Ruspurt II      | 7,00-7,50 | 42R40MR * |
| 4,2 x 50mm | Ruspurt II      | 7,00-7,50 | 42R50MR * |
| 4,2 x 55mm | Ruspurt II      | 7,00-7,50 | 42R55MR * |
| 4,5 x 50mm | Ruspurt II      | 7,00-7,50 | 45R50MR * |
| 4,5 x 55mm | Ruspurt II      | 7,00-7,50 | 45R55MR * |
| 4,2 x 50mm | Stainless Steel | 7,00-7,50 | 42R50MS * |
| 4,2 x 55mm | Stainless Steel | 7,00-7,50 | 42R55MS * |
| 4,2 x 45mm | Weatherex II    | 7,00-7,50 | 42R45MW * |
| 4,5 x 65mm | Weatherex II    | 7,00-7,50 | 45R65MW * |

## FLOORING WOOD TO WOOD




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,2 x 35mm | Yellow Zinc     | 7,00-7,50 | 42RH35MY * |
| 4,2 x 40mm | Yellow Zinc     | 7,00-7,50 | 42RH40MY * |
| 4,2 x 45mm | Yellow Zinc     | 7,00-7,50 | 42RH45MY   |
| 4,2 x 50mm | Yellow Zinc     | 7,00-7,50 | 42RH50MY * |
| 4,2 x 55mm | Yellow Zinc     | 7,00-7,50 | 42RH55MY * |
| 4,5 x 65mm | Yellow Zinc     | 7,00-7,50 | 45RH65MY * |
| 4,5 x 75mm | Yellow Zinc     | 7,00-7,50 | 45RH75MY * |
| 4,2 x 40mm | Ruspurt II      | 7,00-7,50 | 42RH40MR * |
| 4,2 x 50mm | Ruspurt II      | 7,00-7,50 | 42RH50MR * |
| 4,2 x 55mm | Ruspurt II      | 7,00-7,50 | 42RH55MR * |
| 4,5 x 65mm | Ruspurt II      | 7,00-7,50 | 45RH65MR * |
| 4,5 x 75mm | Ruspurt II      | 7,00-7,50 | 45RH75MR * |
| 4,2 x 35mm | Stainless Steel | 7,00-7,50 | 42RH35MS * |
| 4,2 x 40mm | Stainless Steel | 7,00-7,50 | 42RH40MS * |
| 4,2 x 45mm | Stainless Steel | 7,00-7,50 | 42RH45MS * |
| 4,2 x 50mm | Stainless Steel | 7,00-7,50 | 42RH50MS * |
| 4,2 x 55mm | Stainless Steel | 7,00-7,50 | 42RH55MS   |
| 4,5 x 75mm | Stainless Steel | 7,00-7,50 | 45RH75MS * |

## FLOORING/DECKING WOOD TO WOOD (SOFT)




| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR. |
|------------|-----------------|-----------|---------|
| 4,2 x 50mm | Weatherex II    | 8,00-8,50 | 42W50MW |
| 4,2 x 55mm | Weatherex II    | 8,00-8,50 | 42W55MW |
| 4,5 x 65mm | Weatherex II    | 8,00-8,50 | 45W65MW |
| 4,5 x 75mm | Weatherex II    | 8,00-8,50 | 45W75MW |
| 4,2 x 50mm | Yellow Zinc     | 8,00-8,50 | 42W50MY |
| 4,2 x 55mm | Yellow Zinc     | 8,00-8,50 | 42W55MY |
| 4,5 x 65mm | Yellow Zinc     | 8,00-8,50 | 45W65MY |
| 4,5 x 75mm | Yellow Zinc     | 8,00-8,50 | 45W75MY |

## STEEL TO STEEL (UP TO 3 OR 4,4MM)



| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,2 x 13mm | Clear Zinc      | 7,77-8,18 | 42OP13MC   |
| 4,2 x 16mm | Clear Zinc      | 7,77-8,18 | 42OP16MC   |
| 4,2 x 19mm | Clear Zinc      | 7,77-8,18 | 42OP19MC * |

## WOOD TO HEAVY STEEL (UP TO 3MM)



| SIZE       | MATERIAL/FINISH | HEAD Ø    | ART.NR.    |
|------------|-----------------|-----------|------------|
| 4,2 x 35mm | Clear Zinc      | 8,00-8,50 | 42GS35MC * |
| 4,2 x 41mm | Clear Zinc      | 8,00-8,50 | 42GS41MC   |
| 4,2 x 65mm | Clear Zinc      | 8,00-8,50 | 42GS65MC * |

**USE SENCO FASTENERS**