



Technical Data Sheet

Material Reference	:	ARL/68 AS Antistatic and Abrasion Resistant Soft Natural Rubber.
Description & Application	:	FOR SPECIFIC APPLICATIONS PLEASE CONTACT APPLIED RUBBER LININGS LIMITED. ARL/68 AS is a highly abrasive resistant soft natural rubber plant lining material, specifically formulated to be antistatic and with good resistance to many acids and chemicals.
Temperature Range	:	-35°C to 80°C (Depending upon conditions and applications).
Specific Gravity	:	1.15
Hardness	:	65° ± 5° SHORE 'A'
Tensile Strength	:	19.2 MPa
Elongation At Break	:	315%
Compression Set	:	17.8%
Electrical Resistivity	:	N/A.
Health & Safety	:	See COSSH assessments
Typical Applications	:	Particularly useful for lining shot blasting equipment (reclaimers etc) where the build up of static can damage the rubber lining.

NOTE :- INFORMATION GIVEN IN GOOD FAITH BUT DETAILS MAY CHANGE WITHOUT PRIOR NOTIFICATION. CUSTOMERS SHOULD MAKE THEIR OWN ASSESSMENTS TO DETERMINE THAT THE MATERIALS ARE SUITABLE FOR SPECIFIC APPLICATIONS