

FELLER

POWER CORDS

goes green



BVH05VVF3G1,00 - BLUE VINYL PHTHALATFREE PVC

Thermoplastic PVC cordage

with excellent mechanical, electrical properties and chemical resistance.

Flame retardant from HB (standard) to VW1, temperature up to 70°C

Plasticiser without phthalates (DOP, DIDP, DINP).

Standards: HD21.5, UL 62

Usage: Replacement of standard PVC.



H05Z1Z1F3G1,00 - HALOGEN FREE THERMOPLASTIC ELASTOMER

Halogen free harmonized thermoplastic elastomer (TPE) cordage

with rubber like appearance and good mechanical and electrical properties and adequate chemical resistance suitable for low fume and smoke applications.

Flame retardant from HB (standard) to VW1, temperature up to 70°C

Standards: HD21.14

Usage: Replacement of PVC.

Austria

Feller GmbH
Wärndorferstraße 3
A-2525 Günselsdorf
Tel.: ++43/2256/623 25 0
Fax: ++43/2256/623 25 7
e-mail: sales@feller-at.com

Great Britain

Feller (UK) Ltd.
Middlefields Ind. Est.,
South Shields, Tyne&Wear
Tel.: ++44/191/455 1048
Fax: ++44/191/456 6603
e-mail: info@feller.co.uk

Hungary

Feller KFT
Sárdi-er 9
H-9700 Szombathely
Tel.: ++36/94/512 730
Fax: ++36/94/512 731
e-mail: feller@mail.datanet.hu

USA

Feller LLC
9100 Industrial Boulevard
Leland, NC 28451
Tel.: ++1/910/383 6920
Fax: ++1/910/383 6921
e-mail: sales@feller-us.com

Hong Kong

Feller - Neumayer Ltd.
Unit 20,9/F, Kwung Tong
No. 1 Hung To Road, Kowloon, HK
Tel.: ++852/280 681 66
Fax: ++852/257 178 00
e-mail: feller-hk@feller-at.com

www.feller-at.com

FELLER

POWER CORDS

goes green



H05BQF3G1,00 - HALOGEN FREE THERMOPLASTIC POLYURETHAN

Halogen free harmonized cordage with thermoset synthetic rubber wires (EPR) and thermoplastic PU jacket

**with extraordinary mechanical properties,
good electrical values and adequate chemical resistance
temperature up to 70°C**

Standards: HD22.10

Usage: Replacement of PVC, heavy mechanical use, coiled cords with high Retractable forces.



H05BBF3G1,00 - HALOGEN FREE THERMOSET SYNTHETIC RUBBER

**Halogenfree harmonized thermoset synthetic rubber (EPR) cordage
with good mechanical and electrical properties and adequate chemical resistance.**

Resistant against hot pressure.

temperature up to 90°C

Standards: HD22.12

Usage: Replacement of PVC, for applications at higher temperature.

Austria

Feller GmbH
Wärndorferstraße 3
A-2525 Günselsdorf
Tel.: ++43/2256/623 25 0
Fax: ++43/2256/623 25 7
e-mail: sales@feller-at.com

Great Britain

Feller (UK) Ltd.
Middlefields Ind. Est.,
South Shields, Tyne&Wear
Tel.: ++44/191/455 1048
Fax: ++44/191/456 6603
e-mail: info@feller.co.uk

Hungary

Feller KFT
Sárdi-er 9
H-9700 Szombathely
Tel.: ++36/94/512 730
Fax: ++36/94/512 731
e-mail: feller@mail.datanet.hu

USA

Feller LLC
9100 Industrial Boulevard
Leland, NC 28451
Tel.: ++1/910/383 6920
Fax: ++1/910/383 6921
e-mail: sales@feller-us.com

Hong Kong

Feller - Neumayer Ltd.
Unit 20,9/F, Kwung Tong
No. 1 Hung To Road, Kowloon, HK
Tel.: ++852/280 681 66
Fax: ++852/257 178 00
e-mail: feller-hk@feller-at.com

www.feller-at.com