



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre,
White Cottage Farm,
Lucas Green Road,
West End
Woking
Surrey
GU24 9LZ
Tel: (+44) 01483 476767
Fax :(+44) 01483 486343

HM 1800 HOD

| | |
|------------------------|--|
| Maximum Sealing Length | 490mm (18ins) |
| Seal Width | 6mm standard |
| Film Thickness | 2 x 1000 gauge (2 x 250 micron) |
| Voltage | 240 Volts, 110 Volt conversion |
| Power Consumption | 560 Watts per seal |
| Fuse Rating | T 3.15 Amp |
| Footprint | 607mm (L) x 190mm (W) x 150mm (H) |
| Weight | 12 Kgs |
| Operation | Hand operated with hold down latch |
| Mounting | Bench or wall mounted |
| Options | Can emboss alphanumeric characters in the seal (for use with 6mm seal only), 3mm wide seal, T-wire for seal-cut-seal, Round wire for cut-and-seal, Rollers and brackets for layflat tubing |



For those applications requiring hand operation and wide opening jaws, the HM1800 series can be supplied in this HOD version. This machine is fitted in standard form with a 6 mm element enabling production of a tamperproof security coded seal, but an optional narrow element can be supplied for reduced sealing times on thicker materials not requiring the embossed code. Dual time control enables both heating and cooling cycle time to be adjusted for different materials and the hold down catch (HOD) releases the operator during the 3-7 second sealing cycle, to prepare the next pack. This machine is simple to maintain with consumable spares being easy to fit and available from stock.