

HULME MARTIN HEAT SEALERS www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre White Cottage Farm Lucas Green Road, West End Woking, Surrey GU24 9LZ Tel: (+44) 01483 476767 Fax :(+44) 01483 486343 Email: sales@hulmemartin.co.uk

STAND UP POUCH / TUBE SEALER



	220
Maximum Sealing Length	320mm
Seal Width	6mm Double Heat
Film sealable	250mu PE, Aluminium laminated
	pouches, most heat sealable
	materials
Voltage	240Volts, 110V conversion
Power Consumption	50W standing 800W heating cycle
Fuse Rating	3.15A Mains – 16A Elements
Foot Print	390mm x 33mmm x 620mm high
Weight	18Kg
Operation	Hand Operated with hold down
	handle
Mounting	Stands on a bench
Finish	Mild Steel with High Gloss white
	powder coat
Adjustable Shelf	Optional
Jaw opening	25mm
Max Bag height	350mm
Max bag height with shelf	250mm

This impulse sealer has been designed to stand up pouches and tubes. It is fitted with a dual electronic timer for control over both the heat and cool cycles. The operation lever locks into position while the welding cycle takes place leaving the operator free to load the next bag to improve productivity. Both of the jaws move simultaneously to ensure the jaws close around the bag without distortion. Each jaw is fitted with a 6mm element, applying the heat from both sides of the bag to ensure a high quality seal, on laminated pouches and Tubes. Tube holders can be manufactured so several tubes can be welded at the same time.

The height of the sealing jaws is adjusted with 2 tri-screws on the back of the machine so the machine slides along the H-Frame upright for infinite adjustment. Larger H-frame stands can be manufactured to meet your requirements.