



HULME MARTIN HEAT SEALERS

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd
Unit 5B, Country Business Centre,
White Cottage Farm,
Lucas Green Road,
West End
Woking
Surrey
GU24 9LZ
Tel: (+44) 01483 476767
Fax :(+44) 01483 486343

HM 3100 CDL Impulse Heat Sealers

Maximum Sealing Length	310mm (12.5ins)
Seal Width	3mm only
Film Thickness	2 x 1000 gauge / 2 x 250 micron
Voltage	240 Volts, 110 Volt conversion
Power Consumption	300 Watts per seal
Fuse Rating	T 3.15 amp
Footprint	400mm (L) x 340mm (W) x 150mm (H)
Weight	14.5 Kgs
Operation	Foot operated via cable and pedal
Mounting	Bench mounted
Options	Rollers and Brackets for layflat tubing



General purpose foot operated machines with many applications. Used extensively by hospitals, laboratories, retailers, engineering and other industries. Simple bench mounting. This CDL model has a dual electronic timer for complete control of the heating and cooling cycle and a cutter to facilitate bag production from lay flat tubing. It also has a cable operated foot pedal which allows increased flexibility of installation. Another advantage is that the foot pedal is of a lever action design which helps to minimise operator effort. This machine is simple to maintain with consumable spares being easy to fit and available from stock.