

HULME MARTIN HEAT SEALERS

www.hulmemartin.co.uk

Hulme Martin Heat Sealers Ltd Unit 5B, Country Business Centre, White Cottage Farm, Lucas Green Road, West End Woking Surrey GU24 9LZ

Tel: (+44) 01483 476767 Fax:(+44) 01483 486343

HM 7600 DL Impulse Heat Sealers

Maximum Sealing Length	770mm (30ins)
Seal Width	3mm standard
Film Thickness	2 x 1000 gauge (2 x 250 Micron)
Voltage	240 Volts, 110 Volt conversion
Power Consumption	360 Watts per seal
Fuse Rating	T 3.15 Amp
Footprint	955mm (L) x 180mm (W) x 190mm (H)
Weight	21 Kgs
Operation	Foot operated via cable and pedal
Mounting	Bench mounted or optional Stand Kit
Options	Stand Kit, Rollers, Brackets and Retainers
	for layflat tubing



Large capacity general purpose foot operated impulse sealing machines for industrial, warehousing and mail order applications. Simple bench mounting or optional stand available. This DL model has a dual electronic timer for complete control of the heating and cooling cycles. It also has a cable operated foot pedal which allows increased flexibility of installation. Another advantage is that the foot pedal is of a lever action design which helps to minimise operator effort. This machine is simple to maintain with consumable spares being easy to fit and available from stock.