

DEMOUNT PRO

Brítísh designed and built for Brítísh groundcare specialísts

600L tank with 6m boom







www.teamsprayers.com

TEAM DEMOUNT PRO

Standard features



Controls

12V 3-Section balanced boom shut off valves and pressure control valve.

Booms


Boom construction: All booms are manufactured from steel tubular sections to guarantee



Electric in cab switching for boom shut off and pressure valves.

Boom height adjustment: Manual 6-8m; Winch 10 and 12m.

strength and durability.



Work station controlling primary functions to operate the sprayer and when cleaning or filling.

Chemical induction: 20L hopper for safe transfer of liquids and powders via a high flow suction system to the main tank, a rotary nozzle for cleaning containers.



Diaphragm pump: High quality poly' diaphragm pump withstands any aggressive plant protection chemicals.

Boom stowage system secures boom assembly in the folded position for safe road

transport.

Break back: All booms are fitted with break back pivot points to protect against unforeseen obstacles.

Transport width:

Folds to compact 1.9m (6m model); 2.4m (12m model).





Large Access for tank filling.

Clean water tank rinse.







Clothes storage:



I5L Clean water supply: For hand washing.

For all PPE equipment.

t. 01353 661 211

TEAM DEMOUNT PROOptional extras

Water suction: Enabling tank filling via the main pump.

Dual covered boom: 5.5 or 6M covered boom system for sensitive areas or windy conditions.

Walk on boom

Bout/Foam Marker System Avoid expensive overspraying on fairways

Computerised spray rate controller automatically adjusts spray application rate to forward speed.

Triple nozzle assemblies enable the operator to select from a choice of 3 nozzle sizes for various applications.

Other optional extras Stainless steel spray lines, retractable hose reel and hand lance kit, GPS boom section switching.



Tank option

400L 600L 800L





www.teamsprayers.com

TEAM DEMOUNT PRO Technical specifications

ltem	Dimension
Tank capacities (L)	400, 600, 800
Pumps (type / L per min)	Poly 2073 / 73
Boom lengths (m)	4, 6, 7, 8, 10, 12
Weight (Kg)	175 (300L x 6m model); 285 (600L x12m model)
Total height (m)	1.6 (6m); 2 (12m)
Total width (m)	1.9 (6m); 2.4 (12m)



Team Sprayers Limited

Unit 3 Lancaster Way Business Park Witchford, Ely, Cambs CB6 3NW Tel: 01353 661 211 Fax: 01353 666 642 Email: sales@team-sprayers.com www.teamsprayers.com

Leaders in the field of application