



Classic2 Communal Door and Panel Specification

All options are fully certified by Secured by Design

1 Door / Panel Size

Up to 1200mm wide and 2200mm high. (Larger doors are available outside SBD certification)

2 Door and panel configuration (see diagrams on website)

3 Glazing / Solid infill

Polycarbonate - 6mm or 10mm

Laminate - 6mm or 10mm

Double Glazed Unit - 24mm

Solid Infill - 10mm or 24mm

4 Hinge

Pivot or Continuous Hinge - Dorma RTS87, LCN 4011 (inward) or LCN 4111 (outward)

5 Lock

2no. iGEM 5000f Maglocks

2no. Securitron M62 Series Maglocks (not SbD approved)

1no. Fulex 'Crime-Beater' multipoint lock, SbD handleset, Euro profile double cylinder

1no. Sashlock, SbD handleset, Europrofile double cylinder

1no. Deadlock, Security Escutcheon, Europrofile double cylinder

6 Ancillary Items

Threshold - 12mm ramped aluminium

Stainless Steel Bolt Through Pull Handle

1no. Stainless steel Bolt through Pull Handle - Straight, 1no. Pushplate

2no. Stainless steel Bolt back to back Pull Handle - Straight

1no. Stainless steel Bolt through Pull Handle - Cranked, 1no. Pushplate

2no. Stainless steel Bolt back to back Pull Handle - Cranked

Painted Trim - 6pcs 50mm or 25mm

Additional keys

Door Stops

Wall mounted rubber buffer

Floor mounted

Bolt-in rail

Concrete-in rail

Bollard

7 Colour

See standard colour range (other colours are available)

Note: Panels can be prepared for access control interface panel (including firemans switch)