



**Our new quick delivery programme “Fastlane“ guarantees
lead times of 5 working days ex works
for selected models of our product range!**

Model	Connections	Plate thickness	Gasket	Frame dimensions
FP05	1“G male thread 1.4571 / 316Ti	0,35	NBR-HT, EPDM-HT	30, 60
FP09	1“G male thread 1.4571 / 316Ti	0,35	NBR-HT, EPDM-HT	30, 60
FP10	2“G male thread 1.4571 / 316Ti alt. DN50 flange connection*	0,35	NBR-HT, EPDM-HT	30, 60
FP16	2“G male thread 1.4571 / 316Ti alt. DN50 flange connection*	0,35	NBR-HT, EPDM-HT	30, 60
FP22	2“G male thread 1.4571 / 316Ti alt. DN50 flange connection*	0,35	NBR-HT, EPDM-HT	30, 60, 110
FP205	DN100 flange rubber lined	0,35	NBR-HT, EPDM	80
FP50	DN100 flange rubber lined	0,35	NBR-HT, EPDM	80

* Execution: warm side- flange on tube, carbon steel; cold side- rubber liner

Plate material 1.4404 or 1.4401 / 316 or 316L

Frame PN10

Max. temperature 150°C

Connection placement All on front header (single-pass)

Fluid category 2

Certification (depends on P*V and fluid category): PED Art. 3-3 (Documentation: FUNKE IOM + Dimension sketch + Manufacturer declaration)
PED Cat. III (Documentation: FUNKE IOM + Dimension sketch + CE Marking + Declaration of conformity)

Coating Funke Standard RAL 5012

**When order is placed until 12 noon CET the units
are ready for dispatch 5 working days after!**

fastlane@funke.de