VHF MARINE TRANSCEIVER O ICOM IC-M25EURO **Buoyant, Stylish** and Easy to Use!







Float 'n' Flash feature plus... a style choice of Marine Blue or Metallic Grey flashes!



Slim, Lightweight, High Performance

USB Charging (Micro-B USB type)

II Hours Operating Time (Typical operation with Tx (Hi): Rx: Standby = 5:5:90)



Large LCD and Simple User-Interface



Buoyant with Flashing Red LED



Optional Speaker Microphone

VHF MARINE TRANSCEIVER

The IC-M25 is extremely lightweight,

weighing only 220g. Its 30.5mm slim

shape buttons are well laid out and provide simple and straightforward

operation. In fact, the IC-M25 LCD

body is extremely comfortable to handle.

Large LCD display and laser cut, curved

screen is 30% larger than its predecessor,

The IC-M25 has a Micro-B USB connector and can be charged with the supplied AC

Third party USB charger products such as

charging smart phones, tablets or digital cameras may be used with the IC-M25*.

* The IC-M25 accepts 5V/1A (Max.) input. Use of third

The IC-M25 floats when dropped in water.

Not only does the LCD and key backlight

on the front panel flash, but also the red

LED light blinks through the rear panel

showing the place of the radio so that it

the IC-M23, allowing you to clearly see

the channel number and status icons.

adaptor, BC-217 in 3 hours (approx.).

cigarette lighters or mobile battery for

Buoyant with flashing red LED

party products is not guaranteed.

can be easily retrieved.

USB Charging

Slim, lightweight, easy to use

11 Hours of Battery Life The built-in 1500mAh lithium-ion battery allows 11 hours (approx.) of long operation*.

* Typical operation with Tx (Hi): Rx: standby=5:5:90

Optional HM-213 Speaker-Mic

The optional waterproof speakermicrophone, HM-213, provides commercial grade convenience while mounting the radio around the waist. The radio floats even when the HM-213 is attached

550mW Audio Output

The IC-M25EURO provides a powerful 550mW (typical) audio output making received voice loud and clear.

Other Features

- IPX7 waterproof construction (1m depth of water for 30 minutes)
- 4-step battery life indicator
- · Dual/Tri-watch functions
- · Instant access to Ch16 or programmable call channel
- · Favourite channel function
- · Monitor function opens noise squelch
- Auto scan function
- · LCD auto backlighting
- AguaQuake[™] draining function

SPECIFICATIONS

GENERAL	
Frequency range Tx	156.000-161.450MHz
Rx	156.000-163.425MHz
HOL version Tx	156.000-161.600MHz
Rx	156.000-163.425MHz
Usable channel groups	INT, USA*, ATIS* channels
	* Depending on version
Type of emission	16K0G3E (FM)
Power supply voltage	3.7V DC nominal
Current drain (at 3.7V DC)	
Tx	2.3A
Rx (Internal SP/External SP)	300mA/200mA (Max. audio)
Operating temperature range	-15°C to +55°C
Antenna impedance	50Ω
Dimensions (W×H×D) (projec-	56.6×134.2×30.5mm
tions not included)	56.6×134.2×30.5mm
	220g
Moight (approximately)	
Weight (approximately)	(With FA-SC59V and MB-133)
Weight (approximately)	
TRANSMITTER	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W*
TRANSMITTER Output power	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version
TRANSMITTER Output power Max. frequency deviation	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz
TRANSMITTER Output power	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version
TRANSMITTER Output power Max. frequency deviation	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz
TRANSMITTER Output power Max. frequency deviation Frequency stability	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD)
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold)
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity Adjacent channel selectivity	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold) 70dB 70dB
TRANSMITTER Output power Max. frequency deviation Frequency stability Spurious emissions Adjacent channel power Residual modulation RECEIVER Sensitivity Squelch sensitivity Adjacent channel selectivity Spurious response	(With FA-SC59V and MB-133) 5W (approx.)/1W/0.5W* * For only FRG version ±5.0kHz ±1.5kHz 0.25µW 70dB 40dB -6dBµ emf typ. (at 20dB SINAD) -6dBµ emf typ. (at threshold) 70dB

ions are subject to change without notice or obligati

Applicable IP Rating

Ingress Protection Standard Water IPX7 (Waterproof protection)

OPTIONS





Floats in water, just like the radio







Communications (Southern) Ltd

116 Missenden Acres, Hedge End, Southampton, SO30 2AQ Tele: 0700 4 RADIOS (723567) or: 01794 723467 (RADIOS) e-mail: sales@commsouthern.co.uk web: www.commsouthern.co.uk



IC-M25EUR