









Everyvalve Ltd
DRUM PUMPS & SUBMERSIBLE VERSION
 Page 26

MA3 Electric Barrel and Container Pump	MA5 Electrical Barrel and Container Pump, Seal-Less SL	MP2 Barrel & Container Pump with Air Driven Motor (ex)
<p>QUANTITY: up to 100 l/min DELIVERY HEAD: Max 8m wg VISCOSITY: Max 300C/poise (mpa.s) approx 40 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) UNIVERSAL MOTOR 400w, 220v, 110v or 42v with switch MOTOR PROTECTION & 5 meters cable with safety plug PUMP TUBES available in : PP, PVDF, SS316 & aluminium IMMERSION DEPTHS : 700, 900 or 1200 mm Special lengths possible up to 2.5m TUBE OUTSIDE : 40mm Dia (PP) 42mm Dia alu 38mm Dia (SS/HC) WEIGHT: (pump with motor) approx 3.5Kg (PP) 7.5kg (SS) PUMP for 220v - VDE + GS</p> 	<p>QUANTITY: up to 90 l/min DELIVERY HEAD: Max 20m wg VISCOSITY: Max 460C/poise (mpa.s) approx 60 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) UNIVERSAL MOTOR 630w, 220v, 115v with switch motor protection & 5 meter cable with safety plug PUMP TUBES available in : PP, PVDF, SS316 & aluminium IMMERSION DEPTHS : 700, 900 or 1200 mm TUBE OUTSIDE : Max 50mm Other sizes as 'B3' model WEIGHT: (pump with motor) approx 4.5Kg (PP) 8.5kg (SS)</p> 	<p>QUANTITY: max 100-200 l/min DELIVERY HEAD: Max 9-18m wc VISCOSITY: Max 3760 C/poise(mpa.s) approx 100 E TEMPERATURE: Max 50°C(PP) 100°C (alu, SS, PVDF) AIR DRIVEN MOTOR with a capacity of approx 300W at 6 barsoperating pressure & 6900 rpm AIR CONNECTION: R 3/8 BSP F PUMP TUBES available in :PP, PVDF, SS316 & aluminium IMMERSION DEPTHS :700, 900 or 1200 mm Special lengths possible up to 2.5m TUBE OUTSIDE : 40/65mm (PP) 55mm alu 38/41/50/55mm Dia (SS) 38mm(HC) WEIGHT: (pump with motor) approx 2.6Kg - 6.5kg ACCESSORIES : airline service equipment - air hose/hose coupling protectors & clips available PUMP for 220v - VDE + GS</p> 
1000mm version (COMPLETE UNIT PRICE BELOW)	1000mm version (COMPLETE UNIT PRICE BELOW)	1000mm version (COMPLETE UNIT)
PP*.....REF:26PMA3PP.PRICE:£700.00	PP*REF: 26PMA5PP...PRICE:£800.00	PP*.....REF:26PB4DAP...PPRICE:£910.00
PVDF..REF:26PMA3PV.PRICE:£900.00	PVDF..REF:26PMA5PV....PRICE:£1000.00	PVDF..REF:26PB4DAPV..PRICE:£1,110.00
SS.....REF:26PMA3SS..PRICE:£970.00	SS.....REF:26PMA5SS....PRICE:£1070.00	SS.....REF:26PB4DASS..PRICE:£1,180.00
AL.....REF:26PMA3AL...PRICE:£660.00	AL.....REF:26PMA5AL....PRICE:£760.00	AL.....REF:26PB4DAAL...PRICE:£870.00
SEAL-LESS SL pump tubes are standard fitted to all above motors. This allows specific application advantages on 1000mm long. Prices include 'DRIVE' & 1,000mm PP Tube Set. Very Heavy duty versions for sumps can be supplied on special client demand.		

Submersible Waste Pump		Submersible SS304 PUMP		Type 205 PP Hand Drum Pump	Ref 26P205	PRICE £28.00								
Auto	Float down to 50mm	Auto	Float Switch down to 50mm		<p>HIGH OUTPUT: Dispenses 250ml each down stroke when fully primed</p> <p>CHEMICAL RESISTANT: Suitable for use with liquid media that is compatible with PP & PTFE (Std. construction materials.)</p> <p>CONVENIENT Weight: 1 Kg Stoke is 435mm.</p> <p>OUTLET: Will align to any angle or direction + optional 20mm Hose Outlet Tail included VERSATILE - Telescopic uptake PP pipe adjusts to 25/210 litre containers with BSP & Trisure collar adaptor as standard. Free hand use also very useful. Fits all common plastic/metal drums. FITTING - Don't over tighten the butterfly collar screw or lose 'O' hose tail outlet. SIZE - Boxed - 520mm * 180mm * 110mm in strong own carton. each complete.</p>									
Voltage	240vAC	Voltage	240 v AC											
Cable	10 meters + plug	Cable	10 meters HO7 RNF + plug											
Outlet	1½" BSPm (Side)	Outlet	1½" BSPm (Side)											
Motor	Oil Double Buna Seal	Motor	Oil Double Nitrile Seals											
Use	Continuous Ambient	Duration	Continuous Duty to 45°C											
Max	Particles up to 20mm	Max	Particles up to 10mm											
Vortex Type		Standard Type	High Pressure Type											
														
Description	Omni	Omni	Omni	Description	Dren	Dren	Dren	Dren	Tika*	Plastic Type	Description	Compac Pump	Description	Compac Pump
26MOM	80/5	160/7	200/8	26MD/26MT	80/7	160/8	250/10	350/12	110/45		26P150	140/7	26P200	190/10
Head	5m	7m	8m	Head	7m	8m	10m	12m	45m		Head	7m	Head	10m
L/min	80	160	200	L/min	80	160	250	350	110		L/min	140	L/min	190
Watts	200	370	550	Watts	200	370	550	750	1000		Watts	300	Watts	650
Body SS	304	304	304	Height	231	300	338	338	304		Body	PP	Body	PP
Body Dia.	177	177	177	Body dia	177	177	177	177	180		HxWxL	280x170x200	HxWxL	280x170x200
Weight	6kg	7kg	7kg	Weight	6kg	7kg	7kg	9kg	9kg		Weight	5 Kg	Weight	6 Kg
Price	£245	£288	£337	Price	£235	£266	£335	£379	£375		Price	£ 190.00	Price	£ 240.00
(*Tika = Well Type) Never run dry. Check 304 usage chemically Max figures given are either one or other. Don't suspend by cable or allow scuffing.											Automatic or Manual mode with intergal non-exposed switch. All pumps must be serviced regularly			
PP Level Switch (Below) i.e. " Plastic Float fitted with loose 5 m cable.														
Ref	26PG03		Watts	240v * 5 amps max			Use	Water - Fix to side to adjust level Caution with waves						
Price	£40.00		Body	PP red 72*153*56mm			Float	Adjust to level	Cable	5 meters Rubber				

PLEASE NOTE : Prices subject to change without prior notice.