

NORBAR TORQUE TOOLS HANDTORQUE™ MULTIPLIER WITH INTEGRAL TORQUE TRANSDUCER AND TRS-65



HANDTORQUE™ MULTIPLIER WITH INTEGRAL TORQUE TRANSDUCER

- A UKAS accredited certificate of calibration is supplied with each multiplier as standard
- When the calibration is performed with a T-Box, TTT, TST, Pro-Log or TTL-HE display the multiplier can be interchanged between similar displays without affecting the validity of the calibration
- Compact dimensions allow easy access and handling
- Anti Wind-Up Ratchet (AVWUR) keeps the multiplier loaded for easier and safe operation
- Integrated transducer for accurate torque application; separate torque display required
- Environmentally sealed to IP55 rating

TRS-65

- Battery Life - 45 hours
- Display - 5 digit LCD 8.8mm high
- Handheld and lightweight
- Ranges of N·m and lbf·ft (as standard)
- Peak and Trough hold
- Environmentally sealed to IP65 rating

HANDTORQUE™ MULTIPLIER WITH INTEGRAL TORQUE TRANSDUCER

Part Number	19108
Accuracy	The nominal output of multiplier will be within +/- 1% of reading
Calibration Units	N·m (as standard)
Calibration Range	400 - 2000 N·m (1450 lbf·ft)
Input Square	1/2"
Output Square	1"
Ratio	25:1
Dimensions	H 240 mm/W 220 mm/ D 72 mm
Weight (Multiplier)	3.5 kg
Weight (Reaction)	0.7 kg

TRS-65

Part Number	43257
Units	N·m & lbf·ft (as standard)
Non Linearity	+/- 0.005% full scale deflection
Offset Stability	0.002 typical (0.008 maximum) +/- % full scale from original offset
Gain Stability	0.003 typical (0.01 maximum) % per annum
Weight	265g
Dimensions	H 152 mm/W 90 mm/ D 34mm

For more details on all Norbar products please contact:

NORBAR TORQUE TOOLS LTD

Beaumont Road, Banbury,
Oxfordshire OX16 1XJ
UNITED KINGDOM
Tel + 44 (0)1295 753600
Email enquiry@norbar.com

www.norbar.com