



Site requirements:

1. White powder coated guard frames
2. Lift mast galvanised with nickel plated chain
3. IP65 rated control box/buttons
4. ABS cladding on platform guards

MezzLift details:

- 250 kg (MWL)
- No. of stops: 2
- Ground to 1st floor height: 3590 mm (inc. sump)
- 1st to 2nd floor height: 0 mm
- Usable platform size: 1300 mm (w) x 1100 mm (d) x 900 mm (h)
- Gate locking system: Electrically Interlocked
- **Hold to run**, push button controls at both levels
 - Floor mounted, no pit required
 - Self-supporting mesh shaft

Electrical supply requirements

240 V, 20 Amp, Single phase supply terminated in a double pole isolator at lower level

UNLESS STATED OTHERWISE, GENERAL TOLERANCES TO ISO 2768 TOLERANCE CLASS 'm' FOR MACHINING & 'v' FOR FABRICATION		Customer Ref.	PH Job Number
Drawn By:	Checked By:	Approved by - Date	Quantity
Date: 29/04/2015		Design State: WorkInProgress	
Title: Thermo fisher Scientific - MezzLift 250 kg Guard Frame Tower		Dimensions: mm	
Material:		Scale on A3: 1:35	
Projection:		Sheet Number: 2 of 24	
Manual Handling Solutions 58, Paige Close, Watlington Kings Lynn, Norfolk, PE33 0TQ Tel 01553811977		Drg No. J_MEZZi_GF_MASTER.iam	Edition A
Part No. GF_MASTER	Reference Q141347 REV B		

DH = Dock height
GH = Gate height
* Minimum structural opening / sump size if required