



**MezzLift details:**

- 250 kg (MWL)
- No. of stops: 2
- Ground to 1st floor height: 4830 (inc sump)
  - 1st to 2nd floor height: 0 mm
- Usable platform size: 1000 (w) x 700 (d)
- Guarding 900 high on non-loading edges of the platform
- Gate locking system: Electrically Interlocked
- **Hold to run**, push button controls at both levels
  - Sump required, 135 mm deep
  - Self-supporting mesh shaft
  - Finish - **Black spray finish**

**Electrical supply requirements**

240 V, 20 Amp, Single phase supply terminated in a double pole isolator at lower level

**Site requirements:**

1. External fire doors to be fitted by main contractor - both levels

GH = Gate height  
 DH = Dock height  
 UP = Usable platform  
 \* Minimum structural opening / sump size if required

Drawn By:			Checked By:		Finish	Quantity	Customer Ref.	PH Job Number
					<b>Black spray finish</b>		Date	Design State
							13/04/2015	WorkInProgress
<b>Title:</b>						Approved by		Dimensions
Manchester - Mezz Light - 250 kg								m m
Goods Lift Assembly								Scale on A3
General Arrangement								1:40
								Projection
								⊙ ▢
Manual Handling Solutions			Drg No.		Edition	Sheet Number		
58, Paige Close, Watlington			82400_MEZZi_GF_MASTER.iam		A	2 of 23		
Kings Lynn, Norfolk PE33 0TQ			Part No		Reference			
Tel 01553811977			GF_MASTER		82400			