

**dual
pumps**

Engine Driven Pressure Washers

Delta



Engine Driven
Pressure Washers

Delta 140 - Honda GX Petrol

Part No.	Engine	Lpm	Bar	Kg
DL140P	GX160 5.5Hp	12	140	43
Dimensions 910L x 565W x 890H (mm)				

- Interpump plunger pump fitted with brass manifold
- Heavy-duty two-piece lance & gun assembly
- 10 metre rubber coated high pressure hose
- 3 metre suction hose with filter
- Fitted with oil alert as standard
- Low pressure chemical injection facility
- Low speed pump driven via reduction gearbox
- Unloader valve with adjustable pressure control



Delta
140
Bar
12
Lpm

Delta 150 - Honda GX Petrol

Part No.	Engine	Lpm	Bar	Kg
DL150P	GX200 6.5Hp	14	150	43
Dimensions 910L x 565W x 890H (mm)				

- Interpump plunger pump fitted with brass manifold
- Heavy-duty two-piece lance & gun assembly
- 10 metre rubber coated high pressure hose
- 3 metre suction hose with filter
- Fitted with oil alert as standard
- Low pressure chemical injection facility
- Low speed pump driven via reduction gearbox
- Unloader valve with adjustable pressure control



Delta
150
Bar
14
Lpm

Delta 200 - Honda GX Petrol

Part No.	Engine	Lpm	Bar	Kg
DL200P	GX340 11Hp	15	200	68
Dimensions 910L x 565W x 890H (mm)				

- Interpump plunger pump fitted with brass manifold
- Heavy-duty two-piece lance & gun assembly
- 10 metre rubber coated high pressure hose
- 3 metre suction hose with filter
- Fitted with oil alert as standard
- Low pressure chemical injection facility
- Low speed pump driven via reduction gearbox
- Unloader valve with adjustable pressure control



Delta
200
Bar
15
Lpm

Delta Stainless Steel - Honda GX Petrol

Part No.	Engine	Lpm	Bar	Kg
DSS14150P	GX200 6.5Hp	14	150	43
Dimensions - 820L x 540W x 490H (mm)				

- Interpump plunger pump fitted with brass manifold
- Heavy-duty two-piece lance & gun assembly
- 10 metre rubber coated high pressure hose
- Stainless Steel trolley with pneumatic wheels
- 3 metre suction hose with filter
- Fitted with oil alert as standard
- Low pressure chemical injection facility
- Low speed pump driven via reduction gearbox
- Unloader valve with adjustable pressure control



Delta
150
Bar
14
Lpm