



## LOMAX RANGE OF QUICK RELEASE COUPLINGS

PART NO	BORE SIZE	END CONN	O/D MAX	LENGTH	WORK MAX	TEST	BUST MIN	A/F	CV FACTOR
04	1/4"	1/4"	1.32"	4.8"	18,000	27,000	49,000	0.88"	0.64
06	3/8"	3/8"	1.5"	4.8"	12,000	18,000	40,000	1.12"	2.26
08	1/2"	1/2"	1.7"	5.7"	10,000	15,000	31,000	1.30"	3.46
12	3/4"	3/4"	2.1"	6.6"	6,000	9,000	21,000	1.38"	6.30
16	1"	1"	2.38"	7.24"	5,000	7,500	20,000	1.62"	10.50
20	1 1/4"	1 1/4"	2.75"	7.68"	4,500	6,750	14,500	1.95"	21.00

### STANDARD FEATURES

MATERIAL: STAINLESS STEEL: MONEL K500: HARDENED STEEL NICKEL PLATED

CONNECTIONS: BSP (M OR F): NPT (M OR F): OTHERS ON REQUEST

SEALS: FLUOROCARBON (VITON): MEDIUM NITRILE (BUNE-N): OTHERS ON REQUEST

TEMP. RANGE: -410 TO +250 DEG. 'C' (DEPENDANT ON SEAL MATL.)