H8000

Relative Humidity Element

The H8000 capacitive polymer element is the latest generation technology, developed to reliably and accurately measure moisture in a wide range of relative humidity applications. This element is the core measurement element of Michell's new range of interchangeable HygroSmart sensors, probes and transmitters.



Highlights

- Linearity ±1.5% RH
- Stability ±1% RH per year
- Operating temperature –40 to +200°C
- · Low thermal hysteresis
- ø0.4mm leg diameter
- · Nominal capacitance 250 pF
- · Low RH hysteresis

Applications

- RH probes
- RH transmitters
- · Portable RH checkers
- Custom OEM RH instruments




Technical Specifications

recrifical opecifications		
Performance Specifications		
RH measurement range		0 to 100% RH
Linearity @ 23°C		±1.5% RH (5 to 95% RH)
RH hysteresis		±1% RH
RH measurement response time		Less than 10 seconds
RH thermal drift (0 to +70°C / 10 kHz)		-0.18% RH/°C -0.24% RH/°C
Maximum mixing ratio		250g water/kg dry air (see envelope)
D factor (tangent of loss angle)		0.02 typical
RH long term stability @ 23°C		< ±1% RH per year
Recommended storage range		+10 to +40°C
Electrical Specifications		
Nominal capacitance (75% RH @ 23°C)		250 pF ±15%
Nominal sensitivity (15 to 85% RH @ 23°C)		0.45 pF / %RH
Operating frequency range		5 / 300 kHz
Operating Specifications		
Operating temperature		-40 to +200°C
Operating pressure		0.04 to 30 bar
Mechanical Specifications		
Weight		0.1g (without cap)
Leg diameter		ø0.4mm
Leg length		12mm, 50mm


Measurement Operating Envelope

The H8000 RH technology operates to the defined technical specifications within the following operating condition envelope:




Product Dimensions

H8000 Element without protection cap



H8000 Element with blue protection cap





The orange HygroSmart symbol is used to identify any Michell RH product which has the latest generation HS3 interchangeable sensor



The blue HygroSmart symbol identifies products using the I7000XP generation interchangeable sensor

Related HygroSmart Products



Advanced interchangeable RH and Temperature Probe

WM281/291

Advanced Wall Mount RH and Temperature Transmitter



Advanced Remote Probe RH and Temperature Transmitter



DT284/294

Advanced 12mm Duct

Mount RH and Temperature

Transmitter



I7000XP

Interchangeable Sensor for Relative Humidity and Temperature

Michell Instruments 48 Lancaster Way Business Park, Ely, Cambridgeshire, CB6 3NW Tel: +44 (0) 1353 658000, Fax: +44 (0) 1353 658199, Email: info@michell.com, Web: www.michell.com/uk

Michell Instruments adopts a continuous development programme which sometimes necessitates specification changes without notice. Issue no: HygroSmart H8000_97482_V2_UK_0216

