

ATTACK 100, 500 & 750

SELECT FLOW NOZZLES



Attack 100
1" BSP Female



Attack 750
Inlet: 2" BSP Male



Attack 500
Inlet: Storz C

**DESIGNED FOR GENERAL FIRE
FIGHTING WITH EXCELLENT
HIGH RISE PERFORMANCE**

- Stainless Steel Spinning Teeth
- Long Range Penetrating Jet
- Dense Wide Angle Fog Pattern
- Variable Flow Rates
- Easily Maintained
- Colours Options Available
- 30% Lighter than Most Comparable Nozzles



Stainless Steel Spinning Turbine Teeth

GENERAL DESCRIPTION

The Delta Attack 100, 500 and 750 represents the state of the art mainline nozzle design, providing a powerful, long range main jet with a coherent stream pattern, combined with high performance water spray patterns.

The computer designed waterway maximises hydraulic efficiency and combines it with the lightest most compact design in its class.

FEATURES

SELECTABLE FLOW RANGE (AT 6 BAR)

Attack 100 = 75, 100 & 125 L/Min (Alternative Flows Available)

Attack 500 = 125, 250, 375 & 500 L/Min

Attack 750 = 285, 460, 600 & 750 L/Min

Cohesive jet and dense water spray pattern at each flow setting. Normal operating range 5 to 8 bar, but fully operational at pressures as low as 3.5 bar

POWERFUL FOG PATTERN - STAINLESS STEEL SPINNING TEETH

Computer designed stainless steel turbine spinning teeth produce an extremely dense fog pattern, giving excellent fire fighting capability and higher degrees of personal protection. Plastic teeth are available as a lower cost option.

NARROW ANGLE CLICK SETTING

The nozzle jet / spray pattern has a single narrow angle click position, which is positive enough to hold the setting in operational use and is easily identifiable in 'blind' fire scenarios.

LOW MAINTENANCE AND RUGGED CONSTRUCTION

The stainless steel ball valve design means only minimal maintenance. An optional stainless steel mesh filter and wide flush setting stop any obstruction of the water flow in use.

A gunmetal version is also available.



Gunmetal Version

TEN YEAR GUARANTEE

Designed and manufactured in the United Kingdom under an ISO 9001 Quality System. Every Delta Attack nozzle is subjected to rigorous quality controls and guaranteed against any manufacturing defect for ten years.

SPECIFICATION

Model Ref	Description
A100-19	Nozzle With 3/4" or 1" BSP Female Swivel Inlet
A100-25	
A500-65	Nozzle With 2 1/2" Male Instantaneous Swivel Inlet
A750-65	Nozzle With 2 1/2" Male Instantaneous Swivel Inlet


Weight: Attack 100 - 1.6kg
Attack 500 - 1.8kg
Attack 750 - 2.4kg

Main Body/Barrel: Hard Anodised Aluminum

Ball Valve: Stainless Steel

Front Bumper: Shockproof Polyurethane

A100-25 230mm (max overall)



A500-65 325mm (max overall)



A750-65 340mm (max overall)

