

# DP3000

## PORTABLE MONITOR



DP3000 Portable Monitor  
c/w DNA2600 Jet/Spray Constant Flow Nozzle

- Lightweight Aluminum
- Compact Folding Base
- 3000 Litres/Minute
- For Water or Foam Application
- Geared Vertical Movement
- Converts to Deck Monitor
- Built in Pressure Gauge



Deck Monitor (Fixed)

## GENERAL DESCRIPTION

The Delta DP3000 Portable Monitor is manufactured in lightweight aluminum and is designed for flows up to 3000 Litres/Minute. It can be used with AFFF Foam/Water Jet Spray Nozzles or Foam Cannons.

It has two inlets which can be fitted with a wide range of international fitting such as 2½" Instantaneous male BS 336, Storz, etc.

The base folds compactly for storage and the quick locking system comprises simple, heavy-duty, dual spring loaded lock pins for quick and easy assembly and positive locking. Vertical movement is by fully enclosed gearing and a safety stop is incorporated at 30° above horizontal.

## FEATURES

The Monitor is convertible to a Deck Monitor by using the top mount flange provided with increased flow to 4500 Litres/Minute and extended elevation to 60° below horizontal.

## TECHNICAL DATA

	Portable	Fixed
Maximum Flow	3000L/Min	4500L/Min
Rotation	320°	360°
Elevation	+30° to +90°	-60° to +90°
Dimensions	Width: 760mm Depth: 840mm Height: 410mm	
Weight	15kg	
Inlet	2 x 2½" BSP Female	4" ANSI 150lb Flange
Outlet	2½" BSP Male	

## NOZZLES

The following jet/spray nozzles are available in durable lightweight alloy.

Model	Type	Flow Litres/Minute
DN-A-2600	Single Flow Adjustable	1900L/Min (or 1140, 2660)
DN-A-2400	Select Flow	1200-1600-2000-2400L/Min
DN-A-2000	Multi Constant Flow	500-1000-1500-2000L/Min
DN-A-1900S	Self Inducing	1900L/Min
DN-A-3800A	Automatic	1135-3785L/Min
DN-A-4500	Select Flow	1900-2800-3800-4800L/Min