

# SMOOTH BORE NOZZLE WITH STACKING TIPS



Smooth Bore  
2.5" Inst Male Inlet  
19mm & 24mm  
Stacking Tips

Made in UK Under ISO 9001 Quality System

- Different Size Stacking Tips
- Stainless Steel Ball Valve
- Long Throws
- Effortless On/Off Control
- Low Maintenance
- Ten Year Guarantee



Smooth Bore 19mm & 24mm Stacking Tips

## GENERAL DESCRIPTION

The Delta Smooth Bore Nozzle enables Fire Fighters to project large volumes of water at relatively low pressure. It has been designed for use in High Rise Buildings where water pressures at the nozzle, via Dry Riser Main Systems, can be less than 4 bar make the Delta Smooth Bore Nozzle idea for these situations. The Straight through waterway greatly reduces problems with blockages due to debris in some fire mains.

## FEATURES

### STAINLESS STEEL BALL VALVE CONTROL

The specially designed stainless steel profiled ball valve allows ease of opening and closing.

### QUICK RELEASE STACKING TIPS

The Delta Smooth Bore Nozzle has a variety of different stacking tips to suit individual applications. The stacked tips available are 15mm & 19mm or 19mm & 24mm (other are available on request). The stacked tips are designed for quick release by unscrewing them until the required size.

### QUICK RELEASE JET/SPRAY

The Delta Smooth Bore Nozzle also has the option of removing the stacked tips and fitting a jet/spray attachment if required.

### LOW MAINTENANCE AND RUGGED CONSTRUCTION

The stainless steel ball valve design means only minimal maintenance.

### TEN YEAR GUARANTEE

Designed and manufactured in the United Kingdom under an ISO 9001 Quality System. Every Delta Smooth Bore nozzle is subjected to rigorous quality controls and guaranteed against any manufacturing defects for ten years.

## PERFORMANCE

Tip Size	Pressure	Flow	Throw (m)
15mm	3 bar	260L/min	??mtrs
	5 bar	320L/min	??mtrs
	7 bar	380L/min	??mtrs
19mm	3 bar	400L/min	??mtrs
	5 bar	515L/min	??mtrs
	7 bar	615L/min	??mtrs
24mm	3 bar	625L/min	??mtrs
	5 bar	815L/min	??mtrs
	7 bar	965L/min	??mtrs

## SPECIFICATION

Model Ref	Description
NFA080102	Nozzle With 2½" Male Instantaneous Swivel Inlet 15mm & 19mm Stacking Tips
NFA080202	Nozzle With 2½" Male Instantaneous Swivel Inlet 19mm & 24mm Stacking Tips
NFA080002	Nozzle With 2½" Male Instantaneous Swivel Inlet Jet/Spray Attachment

Weight: NFA080102 - 1.3kg  
NFA080202 - 1.3kg

Main Body & Tips: Hard Anodised Aluminum  
Ball Valve: Stainless Steel 316

