GBC 2700 SAW

Pipe Cold Cutting Recip Saw



Range: 1" to 20".

Function: cutting up to 45° inclination.

Material: any kind of steel.

• Power: pneumatic or electric.

• Note: The lightweight construction and ease of set up and operation makes it ideal for site work applications. It is capable of cutting most materials including stainless steel.



Electric version available or a conversion kit to easily change pneumatic to electric.











GBC 2700 SAW

			E-Z SAW	E-SAW E
*	Locking tube range	mm	25-508 o/d.	25-508 o/d.
*	Recommended working range	" (o/d.)	1"-20"	1"-20"
**	Torque	kgm	19,0	27,0
***	Max operating temperature	c°	55	55
***	Max noise level	dB	75	75
**	Pneumatic motor power	hp	1,33	-
**	Air consumption	cfm	55-60	-
**	Air working pressure	psi	90	-
*	Air hose connection	inches	3/4"	-
**	Electric motor power	watt	-	1400 (adj.)
**	Alimentation	volt	-	220
**	Frequency	Hz	-	50
***	Idle speed	strokes/min	300	450
*	Unit weight	kg	11,0	9,0
*	Packing dimensions	mm	640x280x130	640x280x130
*	Packing weight	kg	16	14

OPTIONAL ACCESSORIES



Pipe locking vice for 1" to 4". Adjustable blade position to cut angles from 90° to 45°.



Chain vice for 4" to 12" (20" with extra chain)

- All units are supplied as standard with service tools, drawings, instruction manual and warranty certificate.
- Each machine is supplied with a protective metal case.
- We strongly recommend the use of a portable filter lubricator with all our pneumatic models.

- * mechanical data
- ** mathematical data
- *** average data

