

PURGING TAPE PRODUCTS



US & Foreign Patents Pending

PURGE GAS RETAINING TAPE

EZ Zone[®] **Tape** is a purge gas retaining tape used to seal the root gap between pipes to trap argon gas. Composed of two adhesive sections separated by an adhesive-free center zone. The adhesive portion of the tape never comes in contact with the pipe as it is welded; creating a clean, contaminent-free weld. Halogen and chlorofluorocarbon free.

ITEM NO.	DIMENSIONS		ADHESIVE FREE ZONE		CASE QTY.
	ENGLISH	METRIC	ENGLISH	METRIC	CASE QTT.
EZ-ZT 2.5	2.5" x 75'	64 mm x 23 m	1"	25 mm	18
EZ-ZT 4.0	4.0" x 75'	102 mm x 23 m	2"	51 mm	12



EZ Tape[®] is a traditional aluminum tape that can be used for sealing the root gap while purging and sealing pipe ends for transport.Conventional uses include; sealing ducts for heating, air conditioning and refrigeration; and acting as an a vapor barrier. EZ Tape[®] is high temperature resistant, halogen-free and conforms to irregular surfaces.

ITEM NO.	DIMENSIONS		
TIEWINO.	ENGLISH	METRIC	QTY.
EZ-T 2.0	2" x 75'	51 mm x 23 m	24

BACKING TAPE

Fiback[®] fiberglass backing tape is a heat resistant aluminum tape with a woven fiberglass center strip, designed to eliminate or reduce the need for back purging and post weld grinding. Available in **200 AMP** & **600 AMP** formats.



ITEM NO.	D	CASE	
TENINO.	ENGLISH METRIC		QTY.
200 AMP			
AFBT-2.5-200	2.5" x 82'	64 mm x 25 m	5
AFBT-4.0-200	4.0" x 82'	102 mm x 25 m	5
600 AMP		^	
AFBT-2.5	2.5" x 41'	64 mm x 12.5 m	5
AFBT-4.0	4.0" x 41'	102 mm x 12.5 m	5

Aquasol[®] Water Soluble Tape is a pressure sensitive water soluble tape recommended to hold purge dams in position, and when needed to splice two or more pieces of Aquasol[®] paper together. Sold in rolls.

ITEM NO.	ТҮРЕ	DIMENSIONS		CASE OTV
		ENGLISH	METRIC	CASE QTY.
ASWT-1	Roll	1" x 300'	2.5 cm x 92 m	24
ASWT-2	Roll	2" x 300'	5.0 cm x 92 m	12

