



Hexagon Brass Pillars

Type	Thread T	A/F	Length * L mm																																					
HBP	M2	4.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-					
HBP	M2.5	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
Stud Length *			X	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6				
Thread depth			Y	3	3	4	4	5	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6				
HBP	M3	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-			
HBP	M3	5.5	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-		
HBP	M4	7.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-		
HBP	M5	8.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Stud Length *			X	8	8	8	8	8	8	8	8	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10		
Thread depth			Y	3	3	4	5	5	5	8	8	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10

Material: Brass Finish: Electro-nickel plated All dimensions in mm

Hexagon Steel Pillars

Type	Thread T	A/F	Length * L mm																																											
HSP	M3	5.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-						
HSP	M3	5.5	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-				
HSP	M4	7.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
HSP	M5	8.0	5	6	7	8	9	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-		
Stud Length *			X	8	8	8	8	8	8	8	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10				
Thread depth			Y	3	3	4	4	5	6	8	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10			
HSP	M6	10.0	-	-	-	-	-	10	12	13	14	15	16	17	18	20	25	30	35	40	45	50	55	60	70	80	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
Stud Length *			X	-	-	-	-	-	8	8	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	
Thread depth			Y	-	-	-	-	-	6	8	8	8	8	8	8	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10

Material: Mild Steel Finish: Electro-Zinc plated Yellow passivate All dimensions in mm

Hexagon Nylon Pillars

Type	Thread T	A/F	Length * L mm																																																	
HNP	M3	6.0	-	-	-	-	-	10	12	-	-	15	-	-	18	20	25	30	35	40	45	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-			
HNP	M4	8.0	-	-	-	-	-	10	12	-	-	15	-	-	18	20	25	30	35	40	45	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	
HNP	M5	10.0	-	-	-	-	-	10	12	-	-	15	-	-	18	20	25	30	35	40	45	50	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-
Stud Length *			X	-	-	-	-	-	8	8	-	-	8	-	-	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8
Thread depth			Y	-	-	-	-	-	7	9	-	-	10	-	-	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10

Material: Glass reinforced Nylon Colour: Black Max Temp: 110°C All dimensions in mm

How to order: HBP — M3 — 5.0 — 25

* Non-standard body lengths available on request.



Type _____
 Thread _____
 A/F _____
 Length _____

