



Hooped Perimeter Barrier 48mm Diameter Stainless Steel, Concrete In





Perimeter Barriers are designed to help secure site perimeters and provide a permanent obstacle to vehicle access, to mark boundaries, define trolley parks and protect vulnerable door entrances and exits.

Suited to sites where aesthetics and security are equally important, perimeter barriers are commonly found outside car showrooms acting as protection for the cars on the forecourt without impeding a customer's view of the vehicles.

Available in a variety of heights and widths, available as concrete in, bolt down or removable for occasional access.

Galvanised, Stainless steel, galvanised and colour coated available.



Part Number	Description, Height above ground x overall width	Weight (kg)
138 205 098	500 x 500 Stainless Steel Grade 304 - Concrete In	5kg
138 205 118	500 x 1000 Stainless Steel Grade 304 - Concrete In	7kg
138 205 114	500 x 1500 Stainless Steel Grade 304 - Concrete In	9kg
138 205 110	500 x 2000 Stainless Steel Grade 304 - Concrete In	11kg
138 205 142	750 x 1000 Stainless Steel Grade 304 - Concrete In	9kg
138 205 138	750 x 1500 Stainless Steel Grade 304 - Concrete In	11kg
138 205 134	750 x 2000 Stainless Steel Grade 304 - Concrete In	12kg
138 205 128	1000 x 1000 Stainless Steel Grade 304 - Concrete In	11kg
138 205 124	1000 x 1500 Stainless Steel Grade 304 - Concrete In	12kg
138 205 120	1000 x 2000 Stainless Steel Grade 304 - Concrete In	14kg

Product details

- · 2mm wall thickness
- Concrete in 300mm (below ground)
- Brushed finish

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete.

Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete.

Products are guaranteed for 12 months (if installed and used correctly).





