


B BETA FENCE



Securifor Swing gates are available in single and double leaf configuration with a Securifor 358 welded mesh infill to match your fence.

Colors:



SECURIFOR GATE

SPECIFICATIONS

Securifor Panel Specification

Benefits

- Securifor 358 welded mesh provides a high security infill
- Fully adjustable rear hung hinges to prevent tampering
- Lockable ground bolts and anti-lift brackets
- Standard gates open inwards
- Slide bar or mortice lock option
- Available in a wide range of colours and sizes

Applications

Use with Betafence security fencing systems.

Locking system

Consealed mortice lock fitted within the inside of the gate frame complete with interlocking slam plates. Handle or key operated. Slip latch option available

- Slip latch cover plate option available
- Slip latch shroud option available

Features

- Fully adjustable hinges, rear hung to prevent tampering.
- Lockable ground bolts or single and double leaf gates.
- Antilift brackets on double leaf gates.
- Standard gate is inward opening.
- All gates are supplied with free standing posts.
- Optional serrated topping to deter climbing.

For use with the following fencing systems

- Securifor 358
- Securifor 3D
- Securifor 2D

All gates are supplied complete with instructions for assembly and erection.

ASSORTIMENT

Height	Single leaf gate	Double leaf gate
(m)	Width (m)	Width (m)
1.0	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0
1.2	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0
1.5	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0

Height (m)	Single leaf gate Width (m)	Double leaf gate Width (m)
1.8	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0
2.0	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0
2.4	1.0/1.2/1.5	2.0/3.0/4.0/5.0/6.0/7.0/8.0