
Aluminium Hinged Door Screen Domestic



Go to web page

Features

The

Flyscreen Company

- Elegant hinged door screen, which face fits, inside or outside to existing frame, or to the wall outside the reveal. If your door opens out the screen will be fitted on the inside and visa versa.
- White powder coated aluminium, with grey insect mesh as standard.
- Supplied with a single midbar and a kick plate at the bottom to protect the mesh.

Benefits

- Easy access through the doorway.
- Made-to-measure (supplied ready for you to fit) or DIY Kit (experience required). Maximum size 920mm wide x 2100mm high.

Measuring

Measure the width of the aperture plus any bevelled edges on the door frame. Add 27mm* of flat surface on each side (for the screen frame to rest against). Measure the height of the aperture plus any bevelled edges at the top of the door frame.


Add 27mm* of flat surface at the top of the door (for the screen frame to rest against). *If there is not enough flat surface this can be reduced to 10mm, but the frame will overlap some of the aperture.

 $\label{eq:masses} \begin{array}{l} \mbox{Made-to-measure} - \mbox{we will make to the exact size you tell us.} \\ \mbox{DIY Kit} - \mbox{one size available.} \ \mbox{920mm} \times \mbox{2100mm} \end{array}$

Width: Aperture (and bevelled edges) + 54mm of flat surface = _____ mm

Height: Aperture (and bevelled edge) + 27mm of flat surface = _____ mm









Additionally:

Ensure you have an additional 15mm of flat surface for the hinges and 13mm for the magnetic catch – do not include these amounts in the manufacturing measurements you give us.

If your door handle extends more than 8mm beyond the flat surface you will need to build a sub-frame to bring the screen away from the door handle when it is closed. We provide two handles with each door screen, one for each side. The handles extend 22mm from the face of the door screen.



