



Parts Cleaner ...for the safe use of solvent cleaning



Advantages

- stable design
- large work surface in ergonomically correct height
- high load capacity for heavy and big parts
- closed loop for the use of the cleaning liquid
- maximum of work safety for the use of a solvent cleaner
- multi-level filter system for coarse and fine particles prolongs the bath lifetime
- complies with all requirements for cleaning equipment for the use of solvents

Further Information:

The Safety Cleaner L 500 is exceptionally safe and pleasant to use. Besides its ergonomic design, this cleaning table particularly impresses due to its functional fittings.

Further information: (Only available in the UK & Ireland)

Teknox UK Ltd

Phone 44 (0) 3330-129084 E-Mail info@teknox.co.uk | www.Teknox.co.uk

Technical data:

Covered **foot pedal** with self-acting reset device for maximum safety

The **integrated pump** transports the cleaning liquid to the brush and nozzle.

A lid to cover the machine after use.

Parts can be rinsed by using the flexible **nozzle**.

The nozzle can be adjusted to the required position thanks to a versatile jointed hose.

The **big work surface** allows for a barrier-free cleaning process.

Filter set with reusable filter (mesh size 250 µm) segregates fine sediment

Stable, corrosion proof polyethylene **unit base**

Drain valve to discharge used fluid.

A stable **trolley** enables the parts cleaner to be moved around. It provides enough space for the machine and user (optional).

Perforated stainless-steel sink liner, to protect the work surface when cleaning sharp-edge parts (optional).

- External dimensions 1010 x 780 x 1140 mm (W x D x H)
- Usable surface 930 x 545 mm (W x D)
- Work surface height 950 mm
- Load capacity: 250 kg
- Net weight: 55 kg
- Optimum liquid level: 100 Lt
- Minimum liquid level: 60 Lt
- Power input: 35 Watts
- Pump ca: 4 lt/min Flow
- Permitted solvents with a: Flashpoint > 55° C
- Article number 178520

Parts Cleaner 178520

Special features

- **electrical fluid pump (230/50/1)**
- **its flexible, articulated hose enables parts to be rinsed easily**
- **large tank**
- **protected foot pedal**
- **A flow-through brush supports the removal of heavy dirt.**
- **Double-walled cleaning tank for maximum of stability**

The use of a liquid retention system is recommendable in order to comply with water protection laws.

Further information: (Only available in the UK & Ireland)

Teknox UK Ltd

Phone 44 (0) 3330-129084 E-Mail info@teknox.co.uk | www.Teknox.co.uk