

Manual Pipettes



Ergonomic design

This light-weight, ergonomically shaped pipette with comfortable finger-hook assures optimal handling comfort even for long pipetting days. The finger-hook allows you to rest your hand and use a lighter grip during pipetting.

Consistent sample pick up

Magnetic Assist[™] helps find and hold the zero position before aspiration, improving pipetting accuracy and precision, while allowing much lighter plunger springs. Lighter springs coupled with low-drag seals further reduce thumb force.

Reduced thumb impact


A silicone shock absorber inside the tip ejector mechanism reduces thumb impact and stress when ejecting tips.



Ergonomic Masterpiece


Low pipetting forces – highest accuracy

Pipet-Lite[™] with Magnetic Assist[™]



Low force tip ejectionRainingLTS models reduce tip ejection forceson thedramatically. LTS tips incorporate a smallreducesealing area and a positive stop that letsand syou know exactly when the seal is madePipet-

Rainin Pipet-Lite is the most ergonomic manual pipette on the market. From handle-design to the maximum reduction of plunger forces, this pipette ensures light and smooth operation, even after hours of pipetting. Pipet-Lite significantly reduces the risk of repetitive strain injuries (RSIs). The proven "Magnetic Assist" technology offers the lowest plunger forces of any manual pipette. Pipet-Lite is available with LTS and traditional tip shafts. LTS LiteTouch System dramatically reduces tip ejection forces for best ergonomics.




Technical data

Pipet-Lite[™] with Magnetic Assist

The ergonomic masterpiece

Standard equipment

- Magnetic Assist helps locate and hold the zero position before aspiration. Reduced differential between aspiration and blowout spring forces makes both springs significantly lighter
- Ergonomic handle design with a comfortable fingerhook
- Lockable digital volume adjustment: once the volume is set and locked, it cannot be changed accidentally
- Built-in shock absorber on tip ejector reduces thumb impact and stress when ejecting tips
- Quick-release tip ejector
- Available with LTS LiteTouch Tip Ejection System (L-) for use with Rainin LTS tips, and with traditional universal tip/shaft configuration (SL-) for use with universal tips





Pipet-Lite with LTS Dramatically reduces total pipetting forces compared to most traditional pipettes

Specifications

Ordering Information

Cat. No.		Volume Range		
LTS Models	Traditional Models			
L-2	SL-20.	1–2 µL		
L-10	SL-10	0.5–10 µL		
L-20	SL-20	2–20 μL		
L-100	SL-100	10–100 μL		
L-200	SL-200	20–200 μL		
L-300	SL-300	20–300 µL		
L-1000	SL-1000	100–1000 µL		
L-2000	SL-2000	200–2000 μL		
L-5000	SL-5000	500–5000 μL		
L-10ML	SL-10ML	1000 µL- 10 mL		
L-20ML	n/a	2000 µL- 20 mL		
L-START	SL-START	Starter Kits		

Starter Kits – Best Value Easy way to introduce handfriendly pipettes to your lab

Include the most popular size Pipet-Lite or Pipet-Lite SL pipettes: 20, 200, and 1000 μ L, a set of pipette hangers and a rack of tips for each model.



M	Volume	Increment	Accuracy		Precision			
Model	μι	μL	%	μL (±)	%	<u>µL (≤)</u>		
L-2, SL-2	0.2	0.002	12.0	0.024	6.0	0.012		
	1		2.7	0.027	1.3	0.013		
	2		1.5	0.030	0.7	0.014		
L-10, SL-10	1.0	0.02	2.5	0.025	1.2	0.012		
	5.0		1.5	0.075	0.6	0.03		
	10.0		1.0	0.1	0.4	0.04		
L-20, SL-20	2	0.02	7.5	0.15	2.0	0.04		
	10		1.5	0.15	0.5	0.05		
	20		1.0	0.2	0.3	0.06		
L-100, SL-100	10	0.1	3.5	0.35	1.0	0.1		
	50		0.8	0.4	0.24	0.12		
	100		0.8	0.8	0.15	0.15		
L-200, SL-200	20	0.2	2.5	0.5	1.0	0.2		
	100		0.8	0.8	0.25	0.25		
	200		0.8	1.6	0.15	0.3		
L-300, SL-300	30	0.2	2.5	0.75	1.0	0.3		
	150		0.8	1.2	0.25	0.375		
	300		0.8	2.4	0.15	0.45		
L-1000, SL-1000	100	1	3.0	3.0	0.6	0.6		
	500		0.8	4.0	0.2	1.0		
	1000		0.8	8.0	0.15	1.5		
L-2000, SL-2000	200	2	3.0	6.0	0.6	1.2		
	1000		0.8	8.0	0.2	2.0		
	2000		0.8	16.0	0.12	2.4		
L-5000, SL-5000	500	5	2.4	12.0	0.6	3.0		
	2500		0.6	15.0	0.2	5.0		
	5000		0.6	30.0	0.16	8.0		
L-10ML, SL-10ML	1ml	10	5	50.0	0.6	6.0		
	5 ml		1	50.0	0.2	10.0		
	10 ml		0.6	60.0	0.16	16.0		
L-20ML	2 ml	20	5.0	100.0	0.6	12.0		
	10 ml		1.0	100.0	0.2	20.0		
	20 ml		0.6	120.0	0.16	32.0		
Deinin Direct Lite LTO LiteTouch Manaphie Assist and Directions 2008 are								

Rainin, Pipet-Lite, LTS, LiteTouch, Magnetic Assist, and Pipetting 360° are trademarks of Rainin Instrument, LLC.



Quality certificate ISO 9001 Internet: http://www.mt.com/rainin Worldwide service

Specifications subject to change. © 2010 Rainin Instrument, LLC

a METTLER TOLEDO Company

PB-200 Rev C-I

www.mt.com/rainin

For more information