

Product Data Sheet - Scaffold Access

ALTO Allround System Scaffold Stair

ISSUE 01 DATE Oct 19 PAGE 1 of 2

Overview

The Alto Allround System Scaffold Stair is an all-aluminium stair unit designed to be used on system scaffolding with 2.57m bays – typically Layher/Altrad/Instant. A cost-effective, safer alternative to using vertical ladders

Manufactured using structural grade aluminium for strength and reliability, the Alto Allround System Scaffold Stair is a simple and versatile solution for adding staircases to a Layher type system scaffold. Like all Alto products, the Alto Allround System Scaffold Stair is designed to be effective, durable and fully compliant with BS EN 12811.

There are two models in this range covering lift heights of 1.5 and 2.0 metres. Both sizes are also available with Alto Handrails.

Specification

WEIGHT 27.7 kg (2.0m version)

32.8 kg (1.5m version)

1.5m & 2.0m **OPERATING HEIGHTS**

BAY SIZES 2.75m

585mm TREAD WIDTH

635mm **OVERALL WIDTH**

KEY FEATURES - Compatible with Layher/Altrad/Instant


system scaffolding

- Durable, corrosion resistant construction

- Slip resistant platforms and stair treads

- Bolted treads for simple renewal





Unit 19 Howard Road, Park Farm Industrial Estate, Redditch, Worcestershire. B98 7SE +44(0)1527 500577 | sales@altoacees.com | www.altoaccess.com













Product Data Sheet - Scaffold Access

ALTO Allround System Scaffold Stair

ISSUE 01 DATE Oct 19 PAGE 2 of 2

Key Features

- Designed to give scaffolders a cost-effective stair access solution with practical, reliable & compliant equipment.
- The Alto Allround System Scaffold Stair gives a rapidly deployed solution for standard lift heights.
- Made to fit 2.57m bay scaffolding systems e.g. Allround/Ringlok/Instant/Layher. With this product you can quickly install fully compliant stair access to your Layher system scaffold.
- The Alto Allround System Scaffold Stair can be installed without the use of any tools to lock the top hooks onto the transom.
- Two standard models in the range for the most common lift heights of 1.5m and 2.0m.
- Compliant handrails are available for all models.
- Made with standardised components and an all-bolted construction, the Alto Allround System Scaffold Stair can be maintained by any competent operator.
- With a clear width of 585mm and slip-resistant extruded treads, the Alto Allround System Scaffold Stair is comfortable and convenient for the user.







Unit 19 Howard Road, Park Farm Industrial Estate, Redditch, Worcestershire. B98 7SE +44(0)1527 500577 | sales@altoaccess.com | www.altoaccess.com









