


 **INCINER8**
WWW.INCINER8.COM

INCINER8 18-40G TECHNICAL DATASHEET



Our i8-40G builds upon the success of our i8-20G and is a simple and effective incinerator from our small range. It excels due to its suitability for various non-hazardous waste types such as wood, paper, cardboard and other uncontaminated materials. It features advanced chamber technology with an afterburner for the re-burn of harmful emissions with a 2 second retention time to comply with stringent environmental standards.



LOAD CAPACITY

Inciner8 uses four main size guides within our comprehensive range to differentiate our models, from S to XL. This allows us to provide you with a machine that perfectly fits your needs and your waste stream.



CORETEX INSULATION

Coretex insulation - Triple insulation Coretex technology uses a combination of high-density insulation board, custom refractory concrete and thick steel to deliver the ultimate incineration insulation.



TOP LOAD

Top loading allows the waste to be dumped in from above making it easy to access for trucks and machinery. It also allows additional extras such as bin tippers and autoloaders to be used within the operation to improve efficiency and incineration times.



CONTAINER CONFIGURE

Certain Incinerators have the capability to be configured into mobile containerised incineration units. This gives them the benefit of being easy to lock up and secure when at a remote site, as well as being easier to move with added benefits of minimal setup and dismantling time.



TRAILER CONFIGURE

Some of our smaller incinerators can be configured onto trailers. These trailers are country-specific and can be tailored to your needs. This allows extreme portability and can be moved to different locations with very minimal setup time, perfect for constantly moving operations.

Designed and manufactured in Britain to ISO 9001 accredited quality assurance standards. Our machines are widely used across a wide range of sectors, in the UK and around the world, including municipal waste management, manufacturing, mining, and hospitality, as well as tackling serious waste management challenges, including controlled drug disposal, humanitarian response and marine waste.



i8-40G FEATURES

- Small footprint and operating costs.
- Rapid, complete and efficient medical waste disposal
- Patented safety handle for easy access to chamber
- High quality refractory lining and insulation
- Easy to use CE2 control panel
- Programmable temperature control for complete combustion
- Secondary chamber* with 2 second retention time
- Fast pre-heat and continual high temperature performance
- Low energy consumption levels



* Our primary and secondary combustion chambers are constructed from superior grade steel and state-of-the-art monolithic concrete refractory with a unique concave design to prevent cold spots and maximize heat retention during the start-up and combustion processes. When the secondary burner is activated a flame curtain is created which ensures the thermal decomposition of smoke and harmful emissions to produce a clean, odourless vapour exiting the chimney stack.

HT THERMOCOUPLES

Independent control of primary and secondary temperatures via the control panel.

SECONDARY CHAMBER

Retains and re-burns the exhaust gases for minimum of 2 seconds at 850°C.

CHIMNEY STACK

Stainless steel stack for longevity. Fitted with a Velocity Cowl as standard.

PRIMARY CHAMBER

Chamber designed for maximum air flow and circulation which in turn improves efficiency and total burn time.

SAFE USE HANDLES

Easy to open and close loading door. Designed to increase operator safety.

COOL TOUCH CLADDING

Steel cladding to reduce risk of infection and increase longevity of system.

LOW NOX BURNERS

These are some of the cleanest, most efficient burners available today. These can be supplied as gas or oil fired.



HOW INCINERATION WORKS

Incineration is a waste treatment process which utilizes the combustion of organic substances contained within materials to convert waste into ash, heat and flue gas. The ash residue is mostly formed by inorganic constituents of the waste which may take the form of solid lumps or powder.

Heat produced by the incineration process can be fed into a heat exchanger to produce hot water or air which can be used for cleaning or heating purposes. The remaining flue gases are passed through pollution control devices in the form of a secondary combustion chamber or additional filtration (if required) and then expelled to atmosphere.

APPLICATIONS

Our versatile range of medical incinerators are designed for a wide range of waste types. This particular model benefits from a front loading design and very simple operation process. Ideal as a stand-alone machine where limited staff are available to operate.

- General waste
- Plastics & packaging
- Camp waste
- Domestic waste
- Industrial Waste
- Hotels & Resorts
- Mining Operations
- Wood/Construction
- Emergency/Refugee Camps



TECHNICAL SPECIFICATION

model: **i8-40G**

OPERATIONAL SPEC

PHYSICAL SPEC

| | | | |
|---|----------------------|------------------------|---------------------|
| Combustion Chamber Volume (m ³) | 0.36m ³ | Assembled L/W/H (mm) | 1600 x 1300 x 4400 |
| Burn Rate (Kg p/h) | Up to 30Kg | Assembled Weight (Kg) | 1520kg |
| Fuel Consumption (Ltrs p/hour) | 9-11 ltrs | Door Size (mm) | 560 x 560mm |
| Time To Temp | 45-60 mins | Thermocouples (Qty) | 2 |
| Gas retention Time (Seconds) | 2 secs | Steel Thickness (mm) | 3mm |
| Loading Method | Top Load | No. Of Burners | 2 |
| Fuel Options | Light Oil or Gas/LPG | Refractory Composition | Coretex |
| Electricity Supply | 110v or 230v | Operating Footprint | 19.78m ² |
| Control Panel (IP Rating) | IP54 | Cool Touch Cladding | Yes |
| Heat Recovery | No | Viewing Portal | No |
| Auto Ash Removal | No | Tertiary Air Fan | No |
| Auto Loader Compatible | No | | |
| Remote Monitoring | No | | |
| Ash Residue | 3-5% | | |
| Recommended Operational Temperature | 850°C | | |

*The above figures are guidelines ONLY.

Ecoflam burners are renowned worldwide for providing high efficiency and reliable operation with significant energy savings and feature extreme ease of installation, maintenance and flexible boiler-burner matching. This model is fitted with low NOx burners as standard to ensure a complete and clean burn cycle, this reduces installation time and maintenance.

ECOFLAM BURNER SPECIFICATIONS

| PARAMETER (1/2 HR AV) | LIMITS | MEASURED* |
|-----------------------|----------------------|-----------------------|
| Total Dust | 30mg/m ³ | 12mg/m ³ |
| Sulphur Dioxide | 200mg/m ³ | 2.4mg/m ³ |
| Nitrogen Dioxide | 400mg/m ³ | 60mg/m ³ |
| Carbon Monoxide | 100mg/m ³ | 78.3mg/m ³ |

*The above figures are guidelines ONLY.

Ecoflam

- MAX 1-12 have electrical frequency 50-60 Hz
- High efficiency fan ventilation system (HPV)
- Low NOx version class 3 with yellow flame
- Designed in compliance with current regulations
- ISO 9001 and VISION 2000 certification
- All burners are fire tested



NB: picture for illustration purposes only

AVERAGE EMISSIONS / EU STANDARDS

All of our secondary combustion chambers are designed to operate at 850 - 1200°C to re-burn waste gases which prevents smoke, odours and harmful emissions. Dioxins and similar gaseous components are destroyed by a combination of homogeneous high temperatures, excess oxygen levels and sufficient gas residence time in the secondary chamber which our incinerators achieve.

Emissions are largely a product of the waste materials therefore care should be taken when selecting the most appropriate method of pollution control to ensure compliance with your local emissions standards, please discuss this with our sales team if you aren't sure.

**CALL INCINER8 AND START BUILDING SOLUTIONS
TO YOUR WASTE CHALLENGES TODAY!
+44 (0) 1704 884020 OR
EMAIL SALES@INCINER8.COM**

For additional information, or to speak to one of our expert team:

Call
+44 (0) 1704 884020

Email
sales@inciner8.com

 **INCINER8**
www.inciner8.com