

CC33 Transmitter

Flameproof enclosure for explosive gases and vapours in Ex zone 1



CC33 Transmitter

Flameproof enclosure for explosive gases and vapours in Ex zone 1



If combustible gases and vapours are monitored in hazardous areas and there is a requirement for a flameproof gas detector, the CC33 transmitter is a reliable solution. It meets the requirements of ignition protection type „d“ for safe use in Ex zone 1.

Thanks to the proven measuring principle of catalytic combustion, the CC33 detects flammable gases with shortest response times ($t_{90} \leq 9$ s; sensor dependent). This is due to the chimney effect of the sensor housing, which ensures a faster gas flow.

Installation, service and operation

Connection and signal transmission are either via 4-20 mA industrial standard (ACDC-capable) or digitally via the RS-485 interface (Modbus / RTU). Smart Sensor technology simplifies sensor replacement. Maintenance and calibration can be performed by a single person.

When mounted close to the ceiling, a remote calibration adapter can be used for test gas supply without affecting the sensor's chimney effect.

The current measured value including unit, gas type and the menu can be read on the color backlit 2.2-inch display. Operation is done by a magnetic pen. 4 colored LEDs indicate operating, special and alarm status in green, yellow or red.

Reliable measurement & minimal operating costs

The transmitter's built-in electronics compensate for temperature influences and always ensure the highest measurement accuracy. Long-life sensors reduce operating costs.

Variants and options for every application

The CC33 is available as a basic variant in a lacquered aluminium housing and with 10 mm thick bulletproof glass. Alternatively, it is also available in a stainless steel housing (15 mm glass) if the application so requires.

The CC33 can be operated as a stand-alone solution that both detects hazards from combustible gases such as metha-

ne, butane or propane early enough and controls alarms and safety measures.

For an additional on-site alarm, the transmitter is available with an optional buzzer for Ex zone 1, which accompanies the visual alarm (red LEDs and red backlit display) with a loud acoustic signal.

The CC33 can also be optionally configured with three freely programmable relays for the connection of additional visual and audible alarm devices. A colored LED for status indication is provided for each relay.

Also in combination with GfG's powerful controllers, the CC33 is the right choice for monitoring flammable gases and vapors up to the lower explosion limit (LEL) as well as ammonia (vol%).



CC33 with lacquered aluminium housing and explosion-proof buzzer

CC33 Technical Data:

Measuring principle:	Catalytic combustion (CC)	Humidity:	5 to 95 % r. h. ⁵	Weight:	1,60 kg
Measuring ranges:	0 to 100 % LEL ¹ 0 to 4 vol% ²	Air pressure:	80 to 120 kPa ⁵	Approvals / Certifications:	
Gas supply:	Diffusion or gassing per calibration adapter	Output signal:	Analog: 4-20 mA Digital: RS-485	Types of protection:	⊕ II 2G Ex db IIC T6 Gb -20 °C ≤ Ta ≤ +55 °C (without buzzer)
Lifetime of the sensor:	5 years ³	Power supply:	12 to 30 V DC	⊕ II 2G Ex db ib IIC T4/T6 Gb	-20 °C ≤ Ta ≤ +55/+40 °C (with buzzer)
Response time:	$t_{90} \leq 9$ s ⁴	Housing:	Die-cast aluminium		
Temperature:	-25 to +55 °C ⁵	Protection class:	IP67 ⁶		
		Dimensions:	145 x 169 x 129 mm (W x H x D)		

¹ Overview of all gases in the operating instructions, ² For ammonia only, ³ Depending on operating conditions, ⁴ Sensor dependent, ⁵ Depending on sensor und Ex-protection, ⁶ With thread sealing



GfG Gas Detection UK Ltd

Unit 8 | Griggs Business Centre
West Street | Coggeshall
CO6 1NT | Essex | UK

Tel.: +44 (0) 1376 561463
Fax: +44 (0) 1376 561704

www.gfggasdetection.co.uk
sales@gfggas.co.uk