

Dockingstation DS400

for Microtector II Series (G450/G460/G888/G999)



- Fully automatic bump test
- Quick calibration
- Easy handling
- No PC required
- Reduced cost of ownership

Dockingstation DS400

The innovative Dockingstation DS400 is designed for the Microtector II multigas detector series. Its easy handling simplifies your daily bump test, calibration, documentation and charging requirements making the detectors ready for use quickly.

Automatic and quick

Fully automatic bump test and calibration are performed extremely quickly. This saves valuable working time and makes the detectors ready for operation after a very short time.

Easy handling

The easy, menu-driven handling avoids operational errors. The bump test starts automatically once a detector is put in. For adjustment with fresh air and test gas just push one button. Every test is completed by an "Okay" or "Fault" indication of the test result.

Bump test and adjustment includes:

- Visual alarm
- Audible alarm
- Time for activation of Alarm 1
- Time for activation of Alarm 2
- Response time t_{50} or t_{90}

Adjustment

- Zeropoint adjustment
- Sensitivity calibration with test gas
- Purging of sensor

Documentation

You do not need a PC for bump test or adjustment. All relevant data is stored on SD card and can be evaluated later.

Recharging

The dual charge management allows simultaneous charging of both the gas detector G450/G460 and the attached motorised pump plus the new G888 and G999 units.

Gas supply

Gas, air and exhaust gas have their individual connections at the back of the Dockingstation, which also

includes a pump with a capacity of 0.5 l per minute and a demand flow regulator.

Communication

Two RS485 interfaces allow the communication between two Dockingstation DS400 and a PC.

Advantages

- Bump test and adjustment fast and fully automatic
- Easy handling
- OK/Fault indication after each test
- No PC required
- Reduced cost of ownership



Technical data

Dockingstation DS400

Dimensions:

140 x 125 x 225 mm (H x W x D)

Weight:

800 g

Power Supply:

12 Volt DC (6.3 mm jack)

Pump:

Performance 0.5 l/min,
demand flow regulator

Connections:

1 solenoid valve (air/gas)
3 hose connectors (gas/air/exhaust gas)
1 socket for pressure switch 6.3 mm for test gas monitoring
2 interfaces RS485 (RJ45 sockets)

Operation:

via G450/G460/G888/G999 keypad

Readout:

Status display in G450/G460
Alarm LED
Real time clock

Data memory:

SD card for up to 2 GB memory capacity



GfG Gas Detection UK Ltd

Unit 8 | Griggs Business Centre
West Street | Coggeshall
CO6 1NT | Essex | UK

Tel.: +44 (0) 1376 561463
Fax: +44 (0) 1376 561704

www.gfggasdetection.co.uk
sales@gfggas.co.uk