



V16 HC Lumi-Level®

Displays the remaining tank water level in litres on the new V16 HC controller.

V16 HC Flowmeter

Indicates the real world flow rate (litres per minute) and displays the accumulated water use (with reset).

V16 HC DI Saver®

Has the same features as the Auto Fill+Flush, and sends the post flush high TDS water to drain to prolong DI resin life.

V16 HC Auto Fill+Flush

Automatically fills the tank and flushes the membrane to prolong the life of the filters.

V16 HC Auto Fill

Automatically fills the tank. It has two filling settings one time fill or fill on demand.

V16 HC Basic

The upgrade to the V16 Basic HC. The new features include PumpProtect® PumpSmooth® PumpPrecision® PolarityProtect®

V16 HC WFP Link®

Long range radio remote control of the system. The phone app, fob (remote) and controller all work together.

V16 HC Hot Water

Controls the water heating system to stop the system freezing over night as well as indicating the temperature.

V16 HC TDS

Monitors and measures the TDS value and warns when TDS is too high to clean with.



The V16 HC controller is available with any of the variants in any combination.



*PATENT PENDING 1918133.8

V16, WFP LINK, DI SAVER, LUMI-LEVEL, PUMPPROTECT, PUMPSMOOTH, POLARITYPROTECT AND PUMPPRECISION ARE REGISTERED TRADEMARKS OF SPRING (EUROPE) LTD. COPYRIGHT © 2021 SPRING (EUROPE) LTD. ALL RIGHTS RESERVED.