

POWER-LIFT

Tel: 0115 926 9996 Fax: 0115 966 1173 Web: www.powerlift.co.uk

Typical specification pro-forma for
1 off Power-Lift, electro-hydraulic scissor lift.

Model: E
Rated load: kgs. As a uniformly distributed load.
Description of load:
Method of (un)loading:
Nature of operation:
Platform: mm. X mm..
Choice of smooth or slip resisting tear pattern steel deck plate.
Stroke/travel: mm. To be available.
Closed height: Subject to confirmation on pit drawing.
Lifting time:
Power pack: Kw., 3 phase, 400volt, 50Hz..
Choice of inboard or upto 10m. remote in a drip tray with a quick release self sealing coupling.
Control voltage: 24 volts D.C..
Controls: Push button deadman. Complete with up, down and emergency stop.
Anti-trap bar: Fitted.
Safety locks: Fitted.
Surface coating: Blue, RAL5015. 2 component acrylic resin.
Certification: EN1570. Load test and Certificate of conformity or Declaration of incorporation. We draw your attention to EN1570 'Safety requirements for lifting tables'.
Delivery point: Off loading by others.
Lead time: Normally 6-8 working weeks Ex-Works. Please allow 5 days for delivery. Subject to confirmation after receipt of order.
Price: £ exc. VAT each. 30 days net. Delivered carriage paid.
Terms: To G. Power-Lift ApS conditions of business.
Special criteria:
Special features included in above price:

Selection of some of the many optional special features available:
Power pack remote in a drip tray with a quick release self sealing coupling.
Adjustable height limit switch / mechanical stroke restriction.
Adjustment in platform size. / access hatch in platform. Lifting eye bolts.
Barrier rail / gates / auto rising wheelstops / turntables.
Extra control station or emergency stop.
Lift supplied without controls or with different control voltages.
Special IP or EEX?/ ATEX Rated equipment. 304 or 316 stainless steel fabrication.
Hot dip galvanizing with greasable bearings and stainless steel axle and cylinder pins.
Galvanised mesh curtains / Bellows guards / Roller blinds / Rigid enclosure.
Vehicle loading hinged bridging plates.
Gravity roller track or ball top units
Baseframe on wheels / castors or pallet style for fork truck positioning.
Platform support legs at the baseframe with 20mm. of positive adjustment.