

## LIFELINE Batteries

Lifeline™ batteries have been designed for good all-round performance and extended cycle life. They are ideal for all service load and starting requirements in yachts and commercial craft. The use of Absorbed Glass Mat (AGM) technology ensures that the batteries are of the highest possible quality in terms of both performance and safety.

### Benefits:

- Excellent shock & vibration characteristics
- Industry standard sizes
- Sealed construction, no maintenance
- Fully absorbed electrolyte will not leak if damaged
- Can be fitted upright or on its side
- Fast recharge – no current limit providing a voltage-regulated charger is used
- Increased capacity against size
- Up to twice as many cycles as Gel batteries
- Can be stored for up to 2 years before recharge (from fully charged)
- GPL-24T, GPL-27T, GPL-31 also have automotive/marine terminal posts



### Specifications

Lifeline Model Reference	Voltage (V)	Capacity @ 20hr rate (Ah)	Overall Dimensions			Weight kg	Maximum Discharge Current (20°C @ 30secs)	Reserve Capacity @ 25A	Terminals
			Length	Width	Height				
			mm	mm	mm				
GPL- U1T	12	33	195	126	175	10.9	325A	50mins	M6 F
GPL- 1400T	12	43	249	132	174	14.5	850A	n/a	M8 F
GPL- 24T	12	80	283	172	235	25.5	800A	149mins	pos M10 F neg M8 F
GPL- 27T	12	100	333	168	235	29	845A	186mins	pos M10 F pos M8 F
GPL- 31	12	105	329	171	236	31	880A	195mins	pos M10 F neg M8 F
GPL- 4D	12	210	527	220	261	61	1595A	390mins	L-blade M8
GPL- 4CT	6	220	263	181	294	30	1095A	492mins	M8 F
GPL- 8D	12	255	524	278	258	74	1975A	475mins	L-blade M8

DMS technologies, Belbins Business Park, Cupernham Lane, Romsey, Hants., SO51 7JF, UK  
Tel: +44(0) 1794 525400 Fax: +44(0) 1794 525450 e-mail: info@dmstech.co.uk