

RED FLASH™ Batteries for High Rate Applications

Red Flash™ batteries have been designed to produce the very high cranking currents needed for engine starting from the smallest possible battery. The use of Absorbed Glass Mat (AGM) technology ensures that the batteries are of the highest possible quality in terms of both performance and safety.

Benefits:

- Sealed construction, no maintenance
- Excellent shock & vibration characteristics
- Wide operating temperature range
- Fast recharge – no current limit providing a voltage-regulated charger is used
- Fully absorbed electrolyte, minimal risk of leakage if damaged
- Can be fitted upright or on its side
- Small, slim batteries fit into restricted space
- High cranking current provides excellent power to weight ratio
- Ideal for engine start, especially in harsh environments
- Non-hazardous transport by land, sea and air



Specifications

Battery Model	Voltage (V)	Capacity @ 10hr rate	CCA @ -18°C	Overall Dimensions			Weight kg	Maximum Discharge Current (20°C @ 30secs)	Terminals
				Length	Width	Height			
				mm	mm	mm			
RedFlash 900	12	15	156	200	78	134	5.5	255A	M6 F
RedFlash 750	12	26	380	165	173	126	10.9	700A	M6 F
RedFlash 1000	12	26	310	250	97	152	9.0	650A	M6 M
RedFlash 1100	12	37	500	250	97	204	12.5	775A	M6 M
RedFlash 1200	12	42	550	200	169	192	16.0	940A	M6 F
RedFlash 1800	12	51	663	220	121	255	18.5	1115A	M6 M
RedFlash 3500	12	70	930	331	169	177	25.0	1380A	M6 F

RedFlash™ is a trademark of DMS technologies

DMS technologies, Belbins Business Park, Cupernham Lane, Romsey, Hants., SO51 7JF, UK
Tel: +44(0) 1794 525400 Fax: +44(0) 1794 525450 e-mail: sales@dmstech.co.uk