



SBS Batteries

DMS technologies has long been a distributor of the SBS battery range from Enersys. A superior range of valve regulated batteries, with an impressive extended service life, high energy density and shelf life. Manufactured in a range of compact configurations using pure lead technology, the SBS range offers design flexibility where space is at a premium. Advanced plate technology allows SBS batteries to function in the harshest of environments.



Benefits

- Leak resistant dual seal terminal design
- Wide operating temperature range
- High energy density
- Can be mounted in any position, not inverted
- Compact size choices
- Up to two year shelf life @25°C
- Impact resistant case material
- Proven long service life
- Flame retardant to UL94 V-0
- Approved for shipping as non-hazardous

Applications

- Telecommunications Outside Plant
- Telecommunications Wireless
- Cable TV
- Electric Utility/Switchgear
- Offshore
- Uninterruptible Power Supplies

Specifications

Model	Voltage	Capacity @ 10hr rate	Dimensions (mm)			Weight	Brass
			Length	Width	Height	(kg)	Terminal
SBS8	12V	7Ah	138	86	101	2.7	M4 F
SBS15	12V	14Ah	200	77	140	5.7	M6 M
SBS30	12V	26Ah	250	97	156	9.5	M6 M
SBS40	12V	38Ah	250	97	206	12.7	M6 M
SBS60	12V	51Ah	220	121	260	18.5	M6 M

(NB – All capacities at 10hr rate : 20°C to 1.80Vpc)

DMS technologies, Belbins Business Park, Cupernham Lane, Romsey, Hants., SO51 7JF, UKTel: +44(0) 1794 525400Fax: +44(0) 1794 525450e-mail: info@dmstech.co.uk

MAR0001 IssC

www.dmstech.co.uk