spindle travel spindle travel at bottom of vice

Z axis

X and Y axes

NTELLIGENT SYSTEM

Spindle 4.36 mm tool diameter 17000 r.p.m. rotation speed

direct current mechanical power

maximum clearance in Y axis

maximum clearance in X between columns

Clamping systems

concentric holding 100 mm maximum opening of vice 265 mm height of vice jaws 76 mm

Packaging

net weight Noise level

22 kg

52 kg

empty \* when engraving \* peak when engraving \*

Lp Cpeak dB (C) <105

300 mm

unlimited

15 mm

48 mm

210 mm

\* in accordance with Gravograph standards



## optional accessories

- vacuum table and vacuum pump
- 15 mm diameter pen vice
- jewellery vice and prehension jigs
- range of spindles and depth regulating noses
- divider vice for cylinders with maximum diameter 200 mm
- range of mandrel and cones for cylinder prehension
- glass engraving kit

Samira Paradies

**GRAVOGRAPH** 



www.gravograph.com

Gravograph UK Ltd Unit 3 Trojan Business Centre Tachbrook Park Drive Leamington Spa Warwickshire CV34 6RH Tel 01926-884-433 Fax 01926-883-879

LA eq dB (A)  $< 60 \pm 1$ LA eq dB (A) 81±2

## engraving machine



- 225 x 80 mm engraving area.
- Reliability and quality of engraving. IS200 benefits from Gravograph's high standards of manufacture.
- Connected to a computer, it is totally compatible with any PC graphics software generating HPGL files.
- Work area is clear for **easy access to the object** to be engraved.
- Very quiet spindle motor with direct current.
- A complete range of spindles, clamping accessories and tools to suit the evolution of applications.
- Gravograph's software **GravoStyle** allows you to create and carry out your work on the IS200 with efficiency.



- Specific version of IS200 is suitable for flat and cylindrical **engraving**.
- 80 x 225 mm engraving area on items up to 210 mm high and for cylinders up to 200 mm diameter, at +/- 15°.
- Self-centring vice, **large holding capacity** millimetric setting and complete rotary motion on 360° adjustable in height.
- **Depth adjustable vice**, the Y maximum dimension goes from 80 to 265 mm by manual carriage.
- Ideal bulk / capacity ratio. IS200 TX offers you optimum working comfort in a limited space.
- The standard IS 200 can move into IS 200 TX thanks to an adaptation kit.



