

EB400 - Complete with core 1000mm or 1200mm Polyethylene



reflective strips can be added to the neck of the bollard if required. For demarcation pupposes, the EB400 is available ragged only and can be supp

For demarcation puproses, the EB400 is available ragged only and can be supplied as a sleeve only (has no core, to concrete into the ground with a above ground height of 1000mm.

Part Number	Description	Weight (kg)
138 108 550	EB400 - Concrete in	12kg
138 108 551	EB400 - Concrete in complete with white bands	12kg

Product details

- Available concrete in only
- 1000mm or 1200mm height (above ground)
- 90mm diameter core

Concrete in 670mm (below ground) for 1000mm height (above ground)

Steel

Core

EB400

- Concrete in 470mm (below ground) for 1200mm height (above ground)
- Tape colour options Red, orange, yellow, white, or black

Installation & use

Bolt down to a suitable concrete surface. Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

AUTOPA Limited Cottage Leap, Rugby, Warwickshire CV21 3XP

