

Warranty

**24**  
Months

Included



Included



Included



Included



**Technical Highlights:**

- Data Sampling Rate: 1000 Hz
- Accuracy: 0,5 % of Capacity

**Secure Operability**  
due to ergonomically Design

**Overload Protection**  
200 % of full scale

**Turnable Display**  
automatic direction identification

**Attachable to all SAUTER Test Stands**

**Auto-Power-Off**

BASIC



**Real time or Peak Hold Mode** to observe transients or capture peaks

Dimensions:  
L 195 x B 84 x H 35 mm;  
Weight: 600 g

**Stand attachments:** as shown below; Extension rod: 90 mm



Model	Max	Resolution	ISO Calibration Certificate (option)
<b>FK 10</b>	— 10 N	— 0,005 N	- CF 500
<b>FK 25</b>	— 25 N	— 0,01 N	- CF 500
<b>FK 50</b>	— 50 N	— 0,02 N	- CF 500
<b>FK 100</b>	— 100 N	— 0,05 N	- CF 500
<b>FK 250</b>	— 250 N	— 0,1 N	- CF 500
<b>FK 500</b>	— 500 N	— 0,2 N	- CF 500
<b>FK 1k</b>	— 1 000 N	— 0,5 N	- CF 2k