

Warranty

**24
Months**

Included



Included



Included



Included



Option



Technical Highlights:

- Accuracy: 0,5 % of Capacity
- Data Sampling Rate: 500 Hz

STANDARD



Large LCD Display with Backlight, Reverse Display possible.

Peak-Hold Function
Selectable measuring units of NEWTONS, kgf, lbf


Power: **Rechargeable Battery Pack** (6 x 1,5 V)

Can be attached to the **Test Stands** TVE, TVP, THP, THM

Overload Protection: 150 % of capacity

RS 232 output included

Standard Accessories: as shown below.
Extension rod: 52 mm




Windows Software compatible, features sophisticated tools for data analysis, data memory and data processing.

AFH-01
(incl. PC connection)

AFH-FAST
(Data transfer with 10 Hz, otherwise like AFH-01)



Windows Software AFH-01



Dimensions:
L 215 x B 90 x H 43 mm;
Weight: 500 g

Delivered in a **hard carrying case**



| Model | Max | Reso- lution | ISO Calibration Certificate |
|---|---------|-----------------|-----------------------------------|
|  FT 50 and FT 200 with internal sensor | | | |
| FT 50 | 50 N | 0,01 N | CF 500 |
| FT 200 | 200 N | 0,05 N | CF 500 |
|  FT 1k with remote sensor | | | |
| FT 1k | 1 000 N | 0,25 N | CF 2k |