



DMV-350 Ultrasonic Thickness Gauge

The DMV-350 is an economically priced pocket sized light weight ultrasonic thickness gauge for measuring most metals, ceramics, glass and rigid plastics.

11 pre set velocities and adjustable velocity setting for accurate calibration.

Features:

- Pocket sized and light weight
- Range 1.5 ~ 225mm
- 11 pre-set materials
- Adjustable velocity
- Display selectable in mm or inch
- Built-in calibration test plate
- Low Battery Indication
- RS232C interface

Specifications:

- Display: 4 digit 10mm LCD
- Measurement range: 1.5 ~ 225mm (Steel)
- Resolution: 0.1mm
- Accuracy: $\pm 0.5\%n + 0.1$
- Velocity range: 1,000 ~ 9,000 m/s
- Battery: 4 x 1.5V AA (UM4)
- Operating Temperature: 0-50 °C
- Case construction: Rugged ABS plastic
- Dimensions: 120 mm x 62 mm x 30 mm
- Weight: With batteries: 260 g

Accessories:

Carrying Case - 4 x 1.5V AA (UM4) Batteries - Instruction Manual

- | | |
|-------------------------|-----------------------|
| 3-1 Probe connector | 3-2 LCD display |
| 3-3 mm/inch | 3-4 Power |
| 3-5 Material selection | 3-6 Cursor up |
| 3-7 Transducer | 3-8 Calibration |
| 3-9 Cursor down | 3-10 Battery |
| 3-11 Coupling indicator | 3-12 Standard Block |
| 3-13 Velocity Key | 3-14 RS232C Interface |

