



DMV-350 Ultrasonic Thickness Gauge

A compact, simple to use ultrasonic thickness gauge, typically used for corrosion surveys and general thickness checking of metallic and non-metallic materials.

The DMV-350 offers an unrivalled cost / performance ratio.

Features:

- Pocket sized and light weight
- Range 1.5 ~ 225mm
- 11 pre-set materials
- Adjustable velocity
- Display selectable in mm or inch
- Built-in calibration test plate
- Low Battery Indication
- RS232C interface

Specifications:

- Display: 4 digit 10mm LCD
- Measurement range: 1.5 ~ 225mm (Steel)
- Resolution: 0.1mm
- Accuracy: $\pm 0.5\%n + 0.1$
- Velocity range: 1,000 ~ 9,000 m/s
- Battery: 4 x 1.5V AA (UM4)
- Operating Temperature: 0-50°C
- Case construction: Rugged ABS plastic
- Dimensions: 120 mm x 62 mm x 30 mm
- Weight: With batteries: 260 g

Standard Delivery:

Transducer, Ultrasonic Couplant, Batteries, Manual & Carrying Case

- | | |
|-------------------------|-----------------------|
| 3-1 Probe connector | 3-2 LCD display |
| 3-3 mm/inch | 3-4 Power |
| 3-5 Material selection | 3-6 Cursor up |
| 3-7 Transducer | 3-8 Calibration |
| 3-9 Cursor down | 3-10 Battery |
| 3-11 Coupling indicator | 3-12 Standard Block |
| 3-13 Velocity Key | 3-14 RS232C Interface |

