## COSHH SAFETY DATA SHEET - FIBREGLASS GRATING

#### MATERIAL IDENTIFICATION AND USE

Chemical Name Floor Grating made of Fibreglass Reinforced Polyester Common Name Glass Reinforced Plastic Grates. (Fibreglass Grating)

Use Floor, wall.

**INGREDIENTS** 

Fibrous Glass, Polyester Resin, Catalyst (Peroxyester), Styrene, Aluminium Oxide, Pigments. Ingredients are

chemically cured and bonded together.

### HAZARD IDENTIFICATION

Acute Affect None by contact. Dust produced by cutting or grinding can

penetrate the pores of the skin causing itching. Avoid

breathing dust.

Routes of Entry Skin contact or inhalation of dust when cutting.

Medical Note People who have a condition that could be aggravated by

dust should avoid cutting or grinding. Use 3M-respirator mask

No. 4251

First Aid Procedures Skin – Remove person from dust area and shower with soap

and water until itching stops.

Eyes – Flush at once with a sterile eye wash solution.

**CHEMICAL DATA** 

Appearance Solid, flat panels with grid pattern. Green, Grey and Yellow

are standard colours. Sharp edges or grit applied to top surface. Nil odours. Not soluble in water. Specific Gravity 1.6.

#### FIRE FIGHTING MEASURES

Product will burn. Avoid direct fire source. Flash point: none. Flammability limits: none. Extinguishing Media, Water, foam, A, B or C fire extinguishers. Black smoke, Carbon particles.

Use air respirator. Self-extinguishing.

**WASTE DISPOSAL** 

Abide by local laws and procedures. Product is not

considered a hazardous waste.

**HANDLING/CUTTING** Wear masks, and goggles when cutting or grinding. Cover all

exposed parts of the body. Wear gloves when moving or lifting. If using a jigsaw, use Bosch T141HM blade otherwise

use diamond tools.

Anglia Composites Ltd, Unit 5 Stour Valley Business Centre Brundon Lane, Sudbury, Suffolk CO10 7GB

Tel: 01787 377 322 Fax: 01787 377 433 info@angliacomposites.co.uk

# COSHH SAFETY DATA SHEET – URETHANE SEALANT

For sealing cut edges of fibreglass grating.

#### MATERIAL IDENTIFICATION AND USE

COMMON NAME Urethane clear varnish sealant

**USE** Seals cut ends of fibreglass, thus protecting from water

and other liquid intrusion.

**INGREDIENTS** Urethane clear liquid varnish.

**PROTECTION** Wear face mask for large areas or areas where space

is confined. Wear protective gloves. Ensure maximum ventilation. Keep away from children and pets at all

times. Product has a strong odour.

ROUTE OF ENTRY Skin contact.

MEDICAL NOTE Avoid contact with skin and eyes. In cases of contact

with eyes, rinse with water at once and seek medical advice. After contact with skin, wash with plenty of

soap and water.

FIRE MEASURES Product is highly flammable. Keep away from naked

flame and any direct heat source. Do not smoke, eat

food or drink while using this product.

WASTE DISPOSAL Abide by local authority laws and procedures. In all

cases, never dispose of where sealant can creep into

the watercourse.

Anglia Composites Ltd
Unit 5 Stour Valley Business Centre
Brundon Lane
Sudbury
Suffolk CO10 7GB

Tel: 01787 377 322 Fax: 01787 377 433

info@angliacomposites.co.uk