

Removable Parking Post FB (RPP FB) 900mm

Galvanised or Galvanised & Colour





The Removable Parking Post is suitable for areas where occasional access is required. The post is typically locked in place over night and removed during the day. Additional ground sockets are available for storing the post in a convenient location when not in use. The lid has been adapted from a standard RPP to allow the use of FB padlocks.

The RPP FB is available in galvanised and galvanised and coated finish. The post is supplied without a padlock thus allowing the user to specify which FB padlock is required.



Part Number	<u>Description</u>	Lift Weight (kg)	Weight (kg)
138 100 251	60mm Galvanised - Removable	6kg	10kg
138 100 252B	60mm Galvanised & Black - Removable	6kg	10kg
138 100 252Y	60mm Galvanised & Yellow - Removable	6kg	10kg
138 100 252	60mm Galvanised & Colour - Removable	6kg	10kg
138 100 631	76mm Galvanised - Removable	6kg	10kg
138 100 633	76mm Galvanised & Black - Removable	6kg	10kg
138 100 632	76mm Galvanised & Yellow - Removable	6kg	10kg
138 100 634	76mm Galvanised & Colour - Removable	6kg	10kg
138 100 295	90mm Galvanised - Removable	6kg	10kg
138 100 296B	90mm Galvanised & Black - Removable	6kg	10kg
138 100 296Y	90mm Galvanised & Yellow - Removable	6kg	10kg
138 100 296	90mm Galvanised & Colour - Removable	6kg	10kg

Product details

- 900mm (Height above ground)
- 3mm wall thickness
- 60mm, 76mm, and 90mm diameter

- Socket 220mm (below ground)
- Price excludes padlock to secure

Installation & use

Bolt down to a suitable concrete surface.

Telescopic, removable and concrete in are supplied with welded fixing spikes to ensure firm ground anchorage into concrete. Telescopic, removable and concrete in require a suitable excavated hole for installing into concrete. Products are guaranteed for 12 months (if installed and used correctly).



www.autopa.co.uk +44 (0)1788 550556

