TOKEN OPERATED CARWASH MACHINE



Tammer UK specialise in the manufacture of machines. forecourt and can offer a variety programmes of and options, to suit all applications. Either an oil fired heater unit unit can provide constant hot water throughout the wash.ortheunit can have an electric heater which gives hot detergent rinse only, and the rest of the wash is then completed



with cold water. The latter tends to be kinder to paintwork, as constant hot water can dull certain paint finishes.

Token operation deters thieves from breaking into the units to get cash out, and gives greater freedom for the owner to vary the token costs to the customer.

Two programmes are sufficient for most sites, one programme with wax rinse the other without. The more programmes you offer the more confusion you create for the user.

A buzzer sounds 5 seconds before a cycle changes to inform the customer where he is in the programme.

Low maintenance cost and ease of operation makes these units a profitable addition to any forecourt.

SPECIFICATIONS

Voltage.	
Pressure	e1500psi 103bar.
Flow	
Motor	Brook 4 pole motor. 2.2kw 3hp.
Pump	
Hose	
Deterge	ntVariable concentration settings.
Controls	Automatic stop if machine is left unattended.
Dimensi	ons510mm (D) x 1260mm (W) x 1580mm (H).
Weight	Approx. 180kg 396lbs.



- Built to BS 5750 specifications. CE approved.
- 10 year water pump warranty*
- Low speed pump and motor.
- Low maintenance requirement.
- Easy access for servicing.
- Low level protection switches for water, chemical and fuel.
- Stainless steel cabinet, with locking doors.
- Integral frost and fire protection.
- Automatic stop and reset if machine is left unattended.
- Retracting hose reels and overhead booms are optional.

JET WASH SYSTEM

DESCRIPTION

Fixed installation pressure washer unit housed in a stainless steel cabinet, incorporating low maintenance components. Suitable for external installation providing detergent and rinse power wash facility as a stand alone vehicle washing machine.

CONTROLS

Simple in operation with button operated controls. Two wash cycle programmes that give an audible and visual warning of wash cycle changes. Fitted with a non-locking emergency stop button to terminate and reset the programme. Clear operator instructions, both written and diagrammatic, securely attached to the cabinet in a prominent position.

CONTROLS

Wash programmes as shown below:

Programme 1	 2 minute high-pressure cold pre rinse with lance small vehicles). 4 minute low pressure hot wash with detergent through brush. 4 minute high-pressure cold rinse.
Programme 2	 4 minute high-pressure cold pre rinse with lance large vehicles). 5 minute low pressure hot wash with detergent through brush. 5 minute high-pressure cold rinse.

- Provided with automatic frost protection below 4° centigrade. A clearly labelled warning light to indicate that the machine has shut down due to the temperature. An option for fitting of automatic blow down of hose.
- A 5m with 2 off 2.5m swinging boom arms mounted on top.
- Two lances with suitable holsters or brackets for storage. A 1.5m detergent lance with a heavy duty brush. A 1.0m trigger operated rinse lance with a fan jet and shroud.
- Both lances fitted to high pressure hoses, minimum of 10m long from the end of the boom arms.
- Internal detergent storage for a minimum two 25 litre containers.
 Wash to be compatible with a variety of chemical products.
- Cabinet secured with "T" handle locks, to allow easy access to change chemicals.
- Wash incorporates a counter that records hours or number of washes, easily accessible for monitoring purposes.
- 12 months warranty.
- For weeks lead time on delivery and installation of machine from placing of order.
- 15 years life expectancy of machine.
- Manufactured in Britain.



www.tammeruk.co.uk

Tammer UK Ltd

Greenhey Place, Gillibrands Skelmersdale, Lancashire WN8 9SA

Tel: 01695 727994 Fax: 01695 724456 Email: sales@tammer.co.uk